

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : PRISMASTAR GX-5205
Material number : 020456110

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Skin irritation, Category 3, H316
Serious eye damage, Category 1, H318

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Specific target organ toxicity - single exposure, Category 3,
Central nervous system, H336

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
H316: Causes mild skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P280 Wear protective gloves/ protective clothing/ eye
protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with
water for several minutes. Remove contact lenses, if present
and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
Disposal:
P501 Dispose of contents/ container to an approved waste
disposal plant.

Hazardous components which must be listed on the label

Identification
ethyl acetate
isopropyl acetate
butyl lactate
acetone

CAS-No.
141-78-6
108-21-4
34451-19-9
67-64-1

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

PRISMSTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

SECTION 3: Composition/information on ingredients

Substance name : PRISMSTAR GX-5205 neuRez Sonderfall

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
ethanol	64-17-5 200-578-6	Flam. Liq.;2;H225 Eye Irrit.;2A;H319	25 - 50
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	25 - 50
isopropyl acetate	108-21-4 203-561-1	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	20 - 25
butyl lactate	34451-19-9 205-316-4	Eye Irrit.;2;H319 Skin Irrit.;2;H315	1 - 10
aluminium powder (stabilised)	7429-90-5 231-072-3	;; Flam. Sol.;1;H228	1 - 10
cellulose nitrate	9004-70-0	Flam. Sol.;2;H228	1 - 10
acetone	67-64-1	Flam. Liq.;2;H225	1 - 10

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

	200-662-2	Acute Tox.;5;H303 Acute Tox.;5;H313 Eye Irrit.;2A;H319 STOT SE;3;H336	
--	-----------	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

of fire, cans should be stored separately in closed
containments.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive
concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible
absorbent material, (e.g. sand, earth, diatomaceous earth,
vermiculite) and place in container for disposal according to
local / national regulations (see section 13).
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8.

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

the technological safety standards.

Further information on storage conditions

: Protect from humidity and water.

Advice on common storage

: Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethanol	64-17-5	AGW	500 ppm 960 mg/m ³	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m ³	2017-06-08	DE TRGS 900

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m3	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m3	2017-02-01	2017/164/EU
Further information		Indicative			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m3	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
acetone	67-64-1	TWA	500 ppm 1 210 mg/m3	2000-06-16	2000/39/EC
Further information		Indicative			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2015-03-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(l)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethanol	64-17-5	TWA	1 000 ppm	2009-01-01	
ethanol	64-17-5	TWA	1 000 ppm 1 900 mg/m ³	2013-10-08	
ethanol	64-17-5	TWA	1 000 ppm 1 900 mg/m ³	1997-08-04	
ethanol	64-17-5	TWA	1 000 ppm 1 900 mg/m ³	1989-01-19	
ethanol	64-17-5	STEL	1 000 ppm	2013-03-01	
ethanol	64-17-5	PEL	1 000 ppm 1 900 mg/m ³	2014-11-26	
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	2013-10-08	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	1997-08-04	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m ³	1989-01-19	
ethyl acetate	141-78-6	PEL	400 ppm 1 400 mg/m ³	2014-11-26	
isopropyl acetate	108-21-4	TWA	100 ppm	2017-03-01	
isopropyl acetate	108-21-4	STEL	200 ppm	2017-03-01	
isopropyl acetate	108-21-4	TWA	250 ppm 950 mg/m ³	1997-08-04	
isopropyl acetate	108-21-4	TWA	250 ppm 950 mg/m ³	1989-01-19	
isopropyl acetate	108-21-4	STEL	310 ppm 1 185 mg/m ³	1989-01-19	
isopropyl acetate	108-21-4	PEL	250 ppm 950 mg/m ³	2014-11-26	
isopropyl acetate	108-21-4	STEL	310 ppm 1 185 mg/m ³	2014-11-26	
butyl lactate	34451-19-9	TWA	5 ppm	2007-01-01	
butyl lactate	34451-19-9	TWA	5 ppm 25 mg/m ³	2013-10-08	
butyl lactate	34451-19-9	TWA	5 ppm 25 mg/m ³	1989-01-19	
butyl lactate	34451-19-9	PEL	5 ppm 25 mg/m ³	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (total)	10 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	5 mg/m3	2012-07-01	
aluminium powder (stabilised)	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium powder (stabilised)	7429-90-5	PEL (Total dust)	10 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	PEL (respirable dust fraction)	5 mg/m3	2014-11-26	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2008-01-01	
aluminium powder (stabilised)	7429-90-5	TWA	5 mg/m3	2005-09-01	
aluminium powder (stabilised)	7429-90-5	TWA (Total)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (total dust)	15 mg/m3	2011-07-01	
aluminium powder	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

(stabilised)					
aluminium powder (stabilised)	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium powder (stabilised)	7429-90-5	TWA (Respirable fraction)	1 mg/m3	2013-03-01	
aluminium powder (stabilised)	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium powder (stabilised)	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium powder (stabilised)	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	
acetone	67-64-1	TWA	250 ppm	2016-03-01	
acetone	67-64-1	STEL	500 ppm	2016-03-01	
acetone	67-64-1	TWA	250 ppm 590 mg/m3	2013-10-08	
acetone	67-64-1	TWA	1 000 ppm 2 400 mg/m3	1997-08-04	
acetone	67-64-1	TWA	750 ppm 1 800 mg/m3	1989-01-19	
acetone	67-64-1	STEL	1 000 ppm	1989-01-19	

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

			2 400 mg/m3		
acetone	67-64-1	STEL	750 ppm 1 780 mg/m3	2014-11-26	
acetone	67-64-1	C	3 000 ppm	2014-11-26	
acetone	67-64-1	PEL	500 ppm 1 200 mg/m3	2014-11-26	

8.2 Exposure controls**Personal protective equipment**

Eye protection : Goggles

: Eye wash bottle with pure water

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

- : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice :

- : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Water : The product should not be allowed to enter drains, water courses or the soil.

:

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: silver
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 76 °C
Flash point	: -4 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

10.5 Incompatible materialsMaterials to avoid : Acids
Bases
Oxidizing agents

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****ethanol :**

Acute oral toxicity : LD50 Mouse: 3 450 mg/kg

LD50 Rat: 7 060 mg/kg

LD50 Rabbit: 6 300 mg/kg

Acute inhalation toxicity : LC50 Rat: 20 000 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rat: > 2 000 mg/kg

ethyl acetate :

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 18 000 mg/kg

isopropyl acetate :

Acute oral toxicity : LD50 Rat: 6 750 mg/kg

Acute inhalation toxicity : LC50 Rat: 50,6 mg/l
Exposure time: 8 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 17 436 mg/kg
Target Organs: Skin

acetone :

Acute oral toxicity : LD50 Rabbit: 4 700 - 5 800 mg/kg

Mouse: 3 000 mg/kg

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Rat: 9 800 mg/kg

Acute inhalation toxicity : LC50 Rat: 76 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

Skin corrosion/irritation

Product

Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may
degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****ethyl acetate (141-78-6) :**

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l
aquatic invertebrates

isopropyl acetate (108-21-4) :

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 400 mg/l
Exposure time: 96 h

acetone (67-64-1) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21 600 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14: Transport information**14.1 UN number**

- | | | |
|------|---|------|
| ADR | : | 1210 |
| TDG | : | 1210 |
| CFR | : | 1210 |
| IMDG | : | 1210 |
| IATA | : | 1210 |

14.2 Proper shipping name

- | | | |
|------|---|--------------|
| ADR | : | PRINTING INK |
| TDG | : | PRINTING INK |
| CFR | : | PRINTING INK |
| IMDG | : | PRINTING INK |
| IATA | : | PRINTING INK |

14.3 Transport hazard class

- | | | |
|-----|---|---|
| ADR | : | 3 |
| TDG | : | 3 |

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

CFR : 3**IMDG** : 3**IATA** : 3**14.4 Packing group****ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

Tunnel restriction code : (D/E)

TDG

Packaging group : II

Labels : 3

CFR

Packaging group : II

Labels : 3

IMDG

Packaging group : II

Labels : 3

EmS Number : F-E, S-D

IATAPacking instruction (cargo
aircraft) : 364Packing instruction
(passenger aircraft) : 353

Packing instruction (LQ) : Y341

Packaging group : II

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

Labels : 3

14.5 Environmental hazards**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Prohibition/Restriction**REACH - Candidate List of Substances of Very High
Concern for Authorisation (Article 59).: This product does not contain
substances of very high concern
(Regulation (EC) No
1907/2006 (REACH), Article 57).**15.2 Chemical safety assessment**

No data available

SECTION 16: Other information**Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

PRISMASTAR GX-5205

Version 2.0

Revision Date 06.12.2019

Print Date 20.01.2022

H228	: Flammable solid.
H303	: May be harmful if swallowed.
H313	: May be harmful in contact with skin.
H315	: Causes skin irritation.
H316	: Causes mild skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.