

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Agent Stainless Steel bright 180 kgs
Material number : 08835925V

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Skin corrosion/irritation, Category 2, H315
Serious eye damage/eye irritation, Category 1, H318

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Specific target organ toxicity - single exposure, Category 3,
Respiratory system, Central nervous system, H335H336
Specific target organ toxicity - repeated exposure, Category 2,
H373
Aspiration hazard, Category 1, H304

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P314 Get medical advice/ attention if you feel unwell.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or
alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label

Identification	CAS-No.
xylene	1330-20-7
n-butyl acetate	123-86-4
ethyl acetate	141-78-6
acetone	67-64-1
butan-1-ol	71-36-3

SECTION 3: Composition/information on ingredients

Substance name : WS EDELSTAHL-SPRAY/W PERFEKT

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
xylene	1330-20-7 215-535-7	Flam. Liq.;3;H226 Acute Tox.;4;H332 ;2;H315 ;2A;H319 STOT SE;3;H335 STOT RE;2;H373 Asp. Tox.;1;H304	20 - 25
n-butyl acetate	123-86-4 204-658-1	Flam. Liq.;3;H226 STOT SE;3;H336	20 - 25

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	10 - 20
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Acute Tox.;5;H303 Acute Tox.;5;H313 Eye Irrit.;2A;H319 STOT SE;3;H336	10 - 20
butan-1-ol	71-36-3 200-751-6	Flam. Liq.;3;H226 ;2;H315 ;1;H318 STOT SE;3;H335, H336	3 - 10
chromium	7440-47-3 231-157-5	Aquatic Chronic;4;H413	1 - 2,5
nickel	7440-02-0 231-111-4	Skin Sens.;1;H317 Carc.;2;H351 STOT RE;1;H372 Aquatic Chronic;3;H412	0,25 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice : Move out of dangerous area.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

- Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

This information is not available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skinIndicative			
xylene	1330-20-7	STEL	100 ppm 442 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skinIndicative			
xylene	1330-20-7	AGW	100 ppm 440 mg/m ³	2010-08-04	DE TRGS 900

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Peak-limit: excursion factor (category)		2;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)Skin absorption			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	2012-09-13	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Commission for dangerous substancesWhen there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m ³	2017-06-08	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017-02-01	2017/164/EU
Further information		Indicative			
acetone	67-64-1	TWA	500 ppm 1 210 mg/m ³	2000-06-16	2000/39/EC

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2015-03-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
iron	7439-89-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
iron	7439-89-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m ³	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
chromium	7440-47-3	TWA	2 mg/m ³	2006-02-09	2006/15/EC

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Further information		Indicative			
chromium	7440-47-3	AGW (Inhalable fraction)	2 mg/m3	2007-12-27	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		European Union (The EU has established a limit value: deviations in value and peak limit are possible)The threshold value is based on the element content of the corresponding metal.			
chromium	7440-47-3	TWA	2 mg/m3	2006-02-09	2006/15/EC
Further information		Indicative			
chromium	7440-47-3	AGW (Inhalable fraction)	2 mg/m3	2018-06-07	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		European Union (The EU has established a limit value: deviations in value and peak limit are possible)The threshold value is based on the element content of the corresponding metal.			
nickel	7440-02-0	TWA	0,5 mg/m3		DE TRGS 900
nickel	7440-02-0	AGW (Alveolate fraction)	0,006 mg/m3	2017-10-17	DE TRGS 900
Peak-limit: excursion factor (category)		8;(II)			
Further information		For nickel compounds classified as Carc 1A or 1B, see TRGS 910 and TRGS 561. An assessment based on the AGW for nickel metal can be carried out if nickel metal only is present. If nickel-containing dusts are formed during activities in which only surface oxidation is to be controlled, they must be treated as nickel-metal-containing mixtures. When using thermal processes in the presence of oxygen, a formation of oxidic nickel compounds must always be assumed. This is the case, for example, in welding (electrodes or wire) and thermal cutting with or from alloys, in the metal injection of alloys, in the melting and casting of alloys, and in the grinding and separation of alloys with 'spark formation'.			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

	Further recommendations as well as examples of working methods, for which the AGW or the ERB can be used for assessment, are contained in the IFA workbook (code 0537). Commission for dangerous substances When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child Substance sensitizing through the skin
--	--

8.2 Exposure controls**Personal protective equipment**

Eye protection	: Goggles
	: Wear face-shield and protective suit for abnormal processing problems.
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
----------------	---

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: No data available
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 55 °C
Flash point	: -19 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 0,95 g/cm ³
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Viscosity, dynamic : see user defined free text
Viscosity, kinematic : No data available
Flow time : 11 - 14 s at 20 °C
Cross section: 4 mm
Method: DIN 53211

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Other information : No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****xylene :**

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

ethyl acetate :

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 18 000 mg/kg

acetone :

Acute oral toxicity : LD50 Rabbit: 4 700 - 5 800 mg/kg

Mouse: 3 000 mg/kg

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Rat: 9 800 mg/kg

Acute inhalation toxicity : LC50 Rat: 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

chromium :

Acute oral toxicity : LD50 Oral : > 5 000 mg/kg

Acute inhalation toxicity : LC50 : > 5,41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

nickel :

Acute oral toxicity : LD50 Oral : 9 000 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****ethyl acetate (141-78-6) :**

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l
aquatic invertebrates

acetone (67-64-1) :

Toxicity to daphnia and other : (Daphnia magna (Water flea)): 21 600 mg/l
aquatic invertebrates

nickel (7440-02-0) :**Ecotoxicology Assessment**

Long-term (chronic) aquatic : Harmful to aquatic life with long lasting effects.
hazard

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

12.6 Other adverse effects**Product:**

Additional ecological : No data available
information

SECTION 13: Disposal considerations

European Waste Catalogue : 08 01 11 - waste paint and varnish containing organic solvents
or other dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number**

ADR : 1263

TDG : 1263

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

CFR : 1263**IMDG** : 1263**IATA** : 1263**14.2 Proper shipping name****ADR** : PAINT**TDG** : PAINT**CFR** : PAINT**IMDG** : PAINT**IATA** : PAINT**14.3 Transport hazard class****ADR** : 3**TDG** : 3**CFR** : 3**IMDG** : 3**IATA** : 3**14.4 Packing group****ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

Tunnel restriction code : (D/E)

TDG

Packaging group : II

Labels : 3

CFR

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Packaging group : II

Labels : 3

IMDG

Packaging group : II

Labels : 3

EmS Number : F-E, S-E

IATA

Packing instruction (cargo aircraft) : 364

Packing instruction (passenger aircraft) : 353

Packing instruction (LQ) : Y341

Packaging group : II

Labels : 3

14.5 Environmental hazards**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H313	: May be harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Agent Stainless Steel bright 180 kgs

Version 3.1

Revision Date 08.01.2020

Print Date 24.01.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.