

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Concentrate Zincflake 012 180 kgs 14-07012
Material number : 08070425V

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 3, H226
Skin corrosion/irritation, Category 2, H315
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Specific target organ toxicity - single exposure, Category 3, Respiratory system, H335
 Specific target organ toxicity - repeated exposure, Category 2, H373
 Aspiration hazard, Category 1, H304
 Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labelling

Symbol(s)



Signal word

: Danger

Hazard statements

: H226: Flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P316 IF SWALLOWED: Get emergency medical help immediately.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P317 If skin irritation occurs: Get medical help.

P337 + P317 If eye irritation persists: Get medical help.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.


Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
xylene	1330-20-7
butan-1-ol	71-36-3
Naphtha (petroleum), hydrotreated heavy	64742-48-9

SECTION 3: Composition/information on ingredients

Page 3 / 24	102000005101	A member of  ALTANA
-------------	--------------	---

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
xylene	1330-20-7 215-535-7	Flam. Liq.;3;H226 Acute Tox.;4;H332 ;2;H315 ;2A;H319 STOT SE;3;H335 STOT RE;2;H373 Asp. Tox.;1;H304	20 - 25
n-butyl acetate	123-86-4 204-658-1	Flam. Liq.;3;H226 STOT SE;3;H336	10 - 20
aluminium powder (stabilised)	7429-90-5 231-072-3	Flam. Sol.;1;H228	1 - 10
butan-1-ol	71-36-3 200-751-6	Flam. Liq.;3;H226 ;2;H315 ;1;H318 STOT SE;3;H335, H336	1 - 3
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	Flam. Liq.;4;H227 Asp. Tox.;1;H304	1 - 10

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	68308-64-5 939-607-9	Acute Tox.;4;H302 Acute Tox.;3;H311 ;1C;H314 ;1;H318 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,25 - 1
---	-------------------------	--	----------

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

If eye irritation persists, consult a specialist.

If swallowed

: Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, ABC powder, Foam

Unsuitable extinguishing media : High volume water jet

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

No smoking. Keep container tightly closed in a dry and well-

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health				

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

		(MAK-commission).			
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skinIndicative			
xylene	1330-20-7	STEL	100 ppm 442 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skinIndicative			
xylene	1330-20-7	AGW	100 ppm 440 mg/m ³	2010-08-04	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)Skin absorption			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	2012-09-13	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Commission for dangerous substancesWhen there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019-10-31	2019/1831/EU
Further information		Indicative			
n-butyl acetate	123-86-4	TWA	50 ppm 241 mg/m ³	2019-10-31	2019/1831/EU
Further information		Indicative			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m ³	2006-01-01	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Naphtha (petroleum), hydrotreated	64742-48-9	AGW	300 mg/m ³	2017-11-30	DE TRGS 900

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

heavy; Low boiling point ydrogen treated naphtha					
Peak-limit: excursion factor (category)	2;(II)				
Further information	Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900				

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

: Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed
with the producers of the protective gloves.

: The suitability for a specific workplace should be discussed
with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and
concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration
requires.

: In the case of vapour formation use a respirator with an
approved filter.

Environmental exposure controls

General advice :

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

Water : The product should not be allowed to enter drains, water
courses or the soil.

:

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 126 °C
Flash point	: 25 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: ca. 1,2 g/cm ³
Solubility(ies)	
Water solubility	: immiscible
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : see user defined free text

Viscosity, kinematic : No data available

Flow time : 15 - 25 s at 20 °C
Cross section: 4 mm
Method: DIN 53211

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

Heat, flames and sparks.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****xylene :**

Acute inhalation toxicity : The component/mixture is moderately toxic after short term inhalation.

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha :

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates :

Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.

Acute dermal toxicity : The component/mixture is toxic after single contact with skin.

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product**

May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

Solvents may degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****zinc (7440-66-6) :****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates (68308-64-5) :

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

ADR : 1263
TDG : 1263
CFR : 1263
IMDG : 1263
IATA : 1263

14.2 Proper shipping name

ADR : PAINT
TDG : PAINT
CFR : PAINT
IMDG : PAINT
(,Zinc powder, stabilized)
IATA : PAINT

14.3 Transport hazard class

ADR : 3
TDG : 3
CFR : 3
IMDG : 3
IATA : 3

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

14.4 Packing group**ADR**

Packaging group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

TDG

Packaging group : III
Labels : 3

CFR

Packaging group : III
Labels : 3

IMDG

Packaging group : III
Labels : 3
EmS Number : F-E, S-E

IATA

Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packaging group : III
Labels : 3

14.5 Environmental hazards

IMDG : Marine pollutant

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

ADR : Environmentally hazardous

14.6 Special precautions for user**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) :

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted
(xylene)
(aluminium powder (stabilised))
(butan-1-ol)
(Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha)
(Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates)

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022

(Castor oil, sulfated, sodium salt)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H226	: Flammable liquid and vapour.
H227	: Combustible liquid.
H228	: Flammable solid.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

Concentrate Zincflake 012 180 kgs 14-07012

Version 6.0

Revision Date 07.07.2021

Print Date 03.03.2022
