according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA ALUPOR N 513 Aluminium Paste

Product code : 024901PX0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a dangerous substance according to GHS.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to the Globally Harmonised System (GHS).

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl)

esters. May produce an allergic reaction.

2.3 Other hazards

Combustible Solids

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	Flam. Sol. 1; H228	>= 50 - <= 100
2,2' -oxybisethanol	111-46-6 203-872-2 01-2119457857-21	Acute Tox. 4; H302	>= 25 - < 50
dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)	26264-05-1 247-556-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters	97468-33-2 946-101-1	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	>= 0.1 - < 0.25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Do not leave the victim unattended.

No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 21.02.2022 10.12.2019 102000031786 2.0 Date of first issue: 01.08.2019

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Dry sand Suitable extinguishing media :

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas.

Use personal protective equipment. Remove all sources of ignition. Use personal protective equipment.

Avoid dust formation.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Avoid dust formation.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on : Protect from humidity and water. Do not allow to dry.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

storage conditions

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
'		of exposure)	·	
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above			

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

	to these mucontain part fate of any pand the bod particle. HSI termed 'inha fraction of a and is there dust approx	st comply with the ap- icles of a wide range particular particle after y response that it eli- E distinguishes two salable' and 'respirable irborne material that fore available for dep- imates to the fraction	peen assigned specific WELs oppropriate limits., Most indust of sizes. The behaviour, deer entry into the human respicits, depend on the nature a size fractions for limit-setting et., Inhalable dust approximate enters the nose and mouth position in the respiratory train that penetrates to the gas of the paragraphs of the size of	trial dusts position and ratory system, nd size of the purposes ttes to the during breathing ct. Respirable exchange region
	of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term			
	exposure iii	TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	those fraction undertaken General met thoracic and hazardous to concentration inhalable during any dust will these levels to these mucontain partifate of any pand the bod particle. HSI termed 'inhalable termed 'inhalable fraction of all and is thereful dust approximate of the lung. MDHS14/4. WEL, all the short-term elexposure line.	in accordance with the thods for sampling a linhalable aerosols, to health includes due in air equal to or go st or 4 mg.m-3 8-hours to comply with the application of a wide range particular particle after y response that it elies a distinguishes two stable and 'respirable irborne material that fore available for depimates to the fraction Fuller definitions and the proposure limit is listernate should be used.	respirable dust and inhalable which will be collected when he methods described in ME and gravimetric analysis or responsible to the COSHH definition of a set of any kind when present reater than 10 mg.m-3 8-hour TWA of respirable dust. The properties of the prope	sampling is 0HS14/4 spirable, substance at a ur TWA of his means that dust above and exposure trial dusts position and ratory system, and size of the purposes at the during breathing ct. Respirable exchange region of the purposes are trial dusts and exposure trial dusts position and ratory system, and size of the purposes at the during breathing ct. Respirable exchange region of the purpose are trial dusts.
2,2' -oxybisethanol	111-46-6	TWA	23 ppm 101 mg/m3	GB EH40
Further information		pecific short-term ex oposure limit should	posure limit is listed, a figure	three times the

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic	3.95 mg/kg

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue:
 01.08.2019

			effects	
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
2,2' -oxybisethanol	Workers	Inhalation	Long-term local effects	60 mg/m3
	Workers	Skin contact	Long-term systemic effects	43 mg/kg
	Consumers	Inhalation	Long-term local effects	12 mg/m3
	Consumers	Skin contact	Long-term systemic effects	21 mg/kg
	Workers	Inhalation	Long-term systemic effects	44 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
2,2' -oxybisethanol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Water	10 mg/l
	STP	199.5 mg/l
	Fresh water sediment	20.9 mg/kg
	Soil	1.53 mg/kg
	Marine sediment	2.09 mg/kg
	water (intermittent release)	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water

courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Combustible Solids

Self-ignition : not auto-flammable

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : Not explosive

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

Oxidizing properties : No data available

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower

flammability limit

: No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 21.02.2022 2.0

10.12.2019 102000031786 Date of first issue: 01.08.2019

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

Contact with water or humid

air

: This information is not available.

Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Components:

aluminium powder (stabilised):

Acute inhalation toxicity LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

2,2' -oxybisethanol:

Acute toxicity estimate: 500 mg/kg Acute oral toxicity

Method: Converted acute toxicity point estimate

LD50 (Humans): 1,120 mg/kg

Acute inhalation toxicity (Rat): > 4.6 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 21.02.2022

2.0 10.12.2019 102000031786 Date of first issue: 01.08.2019

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

dodecylbenzenesulphonic acid, compound with isopropylamine (1:1):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 21.02.2022

2.0 10.12.2019 102000031786 Date of first issue: 01.08.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phosphoric acid, mono- and bis(C16-20-branched and linear alkyl) esters:

Ecotoxicology Assessment

Long-term (chronic) aquatic

hazard

: May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

14.2 UN proper shipping name

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

: Not applicable

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that

: Not applicable

deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic

pollutants

: Not applicable

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 21.02.2022

 2.0
 10.12.2019
 102000031786
 Date of first issue: 01.08.2019

H319 : Causes serious eye irritation.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



STAPA ALUPOR N 513 Aluminium Paste

Version Revision Date: SDS Number: Print Date: 21.02.2022

2.0 10.12.2019 102000031786 Date of first issue: 01.08.2019

GB/EN