

according to Regulation (EC) No. 1907/2006

HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	HYDRO PELLET 3500
Product code	:	024072HV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	:	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	:	+499152770
Telefax	:	+499152777008
E-mail address of person responsible for the SDS	:	msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture						
Classification (REGULATION (EC) No 1272/2008)						
Long-term (chronic) aquatic hazard, Category 3		H412: Harmful to aquatic life with long lasting effects.				
2.2 Label elements						
Labelling (REGULATION (EC)	No 1272/20	08)			
Hazard statements	:	H412		Harmful to aquatic life with long lasting effects.		
Precautionary statements	:	Preventio P273 Disposal:		Avoid release to the environment.		
		P501		Dispose of contents/ container to an approved waste disposal plant.		

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	REGULATION (EC)	(% w/w)
	Index-No.	No 1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	013-002-00-1		
	01-2119529243-45		
Phosphoric acid, C11-14-isoalkyl	154518-38-4	Skin Irrit. 2; H315	>= 3 - < 10
esters, C13-rich	(52933-07-0)	Eye Dam. 1; H318	
		Aquatic Chronic 2;	
	01-2119976356-25	H411	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move the victim to fresh air.
		No hazards which require special first aid measures.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
		If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.



according to Regulation (EC) No. 1907/2006

HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

If symptoms persist, call a physician.

- **4.2 Most important symptoms and effects, both acute and delayed** None known.
- 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	ABC powder Carbon dioxide (CO2) Water Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Contact with water liberates extremely flammable gas (hydrogen).
		Do not allow run-off from fire fighting to enter drains or water courses.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures				
Personal precautions	:	Use personal protective equipment. Evacuate personnel to safe areas. Use personal protective equipment. Avoid dust formation. Avoid breathing dust.		



according to Regulation (EC) No. 1907/2006


HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 102000029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018
6.2 Enviro	onmental precautions		
Envir	onmental precautions	Prevent further	t from entering drains. leakage or spillage if safe to do so. ontaminates rivers and lakes or drains inform orities.
6.3 Metho	ods and material for co	ontainment and clea	ning up
Meth	ods for cleaning up	: Use mechanica Do not use a va	l handling equipment. acuum cleaner.
		Do not flush wit Keep in suitable	h water. e, closed containers for disposal.

6.4 Reference to other sections

SECTION 7: Handling and storage

	ions for safe handling on safe handling	g :	•	urfaces. yes. ection 8.
	on protection against explosion	:	regulations. Avoid dust formation. Provide at places where dust is formed	appropriate exhaust ventilation d.
Hygiene	e measures	:	When using do not eat or drin Wash hands before breaks ar	
Require	ons for safe storage, i ements for storage nd containers	inclu :	uding any incompatibilities Keep container tightly closed place. Containers which are o resealed and kept upright to p installations / working materia technological safety standard	opened must be carefully prevent leakage. Electrical Ils must comply with the
	information on conditions	:	Protect from humidity and wa	ter.
Advice	on common storage	:	Do not store together with oxi Never allow product to get in storage. Keep away from oxidizing age	, i i i i i i i i i i i i i i i i i i i
			4 / 15	A member of 🜔 ALTANA





HYDRO PELLET 3500

Version	Revision Date: 05.04.2022	SDS Number:	Print Date: 06.04.2022
3.0		102000029889	Date of first issue: 06.08.2018
	er information on ge stability	0.	aterials in order to avoid exothermic reactions. on if stored and applied as directed.

7.3 Specific end use(s) This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40	
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				
		TWA (Respirable fraction)	4 mg/m3	GB EH40	
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				
		TWA (inhalable dust)	10 mg/m3	GB EH40	
Further information	dust) For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes				

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022			rint Date: 06.04.2022 Date of first issue: 06.08.2018	
Furth	er information	fraction of air and is therefor dust approxim of the lung. F MDHS14/4., Y WEL, all the r short-term ex exposure limi For the purpor those fraction undertaken in General meth thoracic and is hazardous to concentration inhalable dus any dust will I these levels. to these musi contain partice fate of any pa and the body particle. HSE termed 'inhala fraction of air and is therefor dust approxim of the lung. F MDHS14/4., Y	able' and 'respirat borne material that ore available for de nates to the fraction uller definitions are Where dusts content relevant limits shout to should be used. TWA (Respirable dust) bases of these limits in accordance with nods for sampling inhalable aerosols health includes d in air equal to or at or 4 mg.m-3 8-h be subject to COS Some dusts have to comply with the cles of a wide range articular particle aff response that it en distinguishes two able' and 'respirat borne material that ore available for de nates to the fraction uller definitions are Where dusts content	ble'., Inhalable dust approxima at enters the nose and mouth of eposition in the respiratory tra- on that penetrates to the gas end ad explanatory material are give ain components that have the ould be complied with., Where ed, a figure three times the lor	during breathing ct. Respirable exchange region ven in ir own assigned no specific ng-term GB EH40 e dust are sampling is HS14/4 spirable, substance at a ur TWA of his means that dust above s and exposure trial dusts position and ratory system, nd size of the purposes tes to the during breathing ct. Respirable exchange region ven in ir own assigned
			it should be used.	ed, a figure three times the lor	ig-term

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	· ·			
Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
Phosphoric acid, C11- 14-isoalkyl esters, C13-rich	Workers	Inhalation	Long-term systemic effects	34.94 mg/m3
	Workers	Skin contact	Long-term systemic effects	100.13 mg/kg
	Consumers	Inhalation	Long-term systemic effects	10.43 mg/m3



according to Regulation (EC) No. 1907/2006

HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 10200002988		nt Date: 06.04.2022 e of first issue: 06.08.2018	3	
		onsumors Sk	kin contact	l ong-torm systemic	60.08 mg/kg	1

	Consumers	Skin contact	Long-term systemic effects	60.08 mg/kg
	Consumers	Ingestion	Long-term systemic effects	6.01 mg/kg
2,2',2"-nitrilotriethanol	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Skin contact	Long-term systemic effects	7.5 mg/kg
	Workers	Skin contact	Long-term local effects	0.14 mg/cm2
	Consumers	Inhalation	Long-term local effects	0.4 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3.3 mg/kg
	Consumers	Skin contact	Long-term systemic effects	2.66 mg/kg
	Consumers	Skin contact	Long-term local effects	0.07 mg/cm2

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
Phosphoric acid, C11-14-isoalkyl	Fresh water	0.00631 mg/l
esters, C13-rich		_
	Fresh water sediment	0.113 mg/kg
	Intermittent water release	0.0631 mg/l
	Marine water	0.000631 mg/l
	Marine sediment	0.0113 mg/kg
	STP	10 mg/l
	Soil	0.0188 mg/kg
2,2',2"-nitrilotriethanol	Soil	0.151 mg/kg
	Fresh water	0.32 mg/l
	Fresh water sediment	1.7 mg/kg
	clarification plant	10 mg/l
	Marine water	0.032 mg/l
	Marine sediment	0.17 mg/kg

8.2 Exposure controls

Personal protective equipment						
Eye protection	:	Tightly fitting safety goggles				
Hand protection Material	:	Protective gloves				
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to				
		7/16				



according to Regulation (EC) No. 1907/2006

HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 102000029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018
Skin	and body protection		ity for a specific workplace should be discussed oducers of the protective gloves.
		Choose bo	vious protective suit dy protection according to the amount and on of the dangerous substance at the work place.
Resp	iratory protection	requires.	e breathing protection if workplace concentration
Envi	ronmental exposure o	ontrols	
Wate	r	: The product courses or	t should not be allowed to enter drains, water the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: pellets
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
рН	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Combustible Solids
Self-ignition	: No data available
Auto-ignition temperature	: No data available
Smoldering temperature	: No data available
Decomposition temperature	: No data available

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 3500

Vers 3.0	sion	Revision Date: 05.04.2022	SDS N 102000	umber: 029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018
	Explosiv	ve properties	: No	data available	
	Oxidizin	g properties	: No	data available	
		xplosion limit / Upper bility limit	: No	data available	
		xplosion limit / Lower bility limit	: No	data available	
	Vapour	pressure	: No	data available	
	Relative	vapour density	: No	data available	
	Relative	density	: No	data available	
	Density		: No	data available	
	Bulk der	nsity	: No	data available	
	Solubilit Wate	y(ies) er solubility	: ins	oluble	
	Solubilit	y in other solvents	: No	data available	
	Partition octanol/	coefficient: n- water	: No	data available	
	Decomp	oosition temperature	: No	data available	
	Viscosit	y, dynamic	: No	data available	
	Viscosit	y, kinematic	: No	data available	
	Flow tim	e	: No	data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.



according to Regulation (EC) No. 1907/2006

HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 102000029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018	
		Stable under	recommended storage conditions.	
		Dust may for	m explosive mixture in air.	
10.4 Co	nditions to avoid			
Cor	nditions to avoid	: No data avai	lable	
10.5 Incompatible materials				
	terials to avoid	: Acids Bases Oxidizing ag Water	ents	
10.6 Ha	zardous decomposition	products		
Cor air	ntact with water or humid	: This informa	tion is not available.	
The	ermal decomposition	: This informa	tion is not available.	
	N 11. Tovicological i			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Product:


Remarks: May cause skin irritation and/or dermatitis.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich: Result: Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.





HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

Product:

Result: No eye irritation

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich: Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product: Remarks: No data available

SECTION 12: Ecological information


12.1 Toxicity

Components:

Phosphoric acid, C11-14-isoalkyl esters, C13-rich:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 24 mg/l
		Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6.31 mg/l





HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 102000029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018			
aquatic invertebrates		Exposure tim	ie: 48 h			
Toxic	Toxicity to algae :		EC50 (algae): 150 mg/l Exposure time: 72 h			
	stence and degradab	ility				
	ccumulative potential ata available					
12.4 Mobi No da	lity in soil Ita available					
	Its of PBT and vPvB a	assessment				
<u>Produ</u> Asses	<u>uct:</u> ssment	to be either p	ce/mixture contains no components considered persistent, bioaccumulative and toxic (PBT), or nt and very bioaccumulative (vPvB) at levels of er			
12.6 Othe	12.6 Other adverse effects					
Produ Additi inform	onal ecological	unprofession	ental hazard cannot be excluded in the event of al handling or disposal. quatic life with long lasting effects.			

SECTION 13: Disposal considerations

European Waste Catalogue European Waste Catalogue	:	12 01 04 - non-ferrous metal dust and particles 10 03 21 - other particulates and dust (including ball-mill dust) containing hazardous substances
13.1 Waste treatment methods		
Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. In accordance with local and national regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. In accordance with local and national regulations.





HYDRO PELLET 3500

Version 3.0	Revision Date: 05.04.2022	SDS Number: 102000029889	Print Date: 06.04.2022 Date of first issue: 06.08.2018				
SECTION	N 14: Transport info	ormation					
14.1 UN n	umber						
Not re	egulated as a dangerou	us good					
14.2 UN p	roper shipping name						
Not re	egulated as a dangerou	us good					
14.3 Tran	sport hazard class(es	5)					
Not re	egulated as a dangerou	us good					
14.4 Pack	ing group						
Not re	egulated as a dangerou	us good					
14.5 Envi	ronmental hazards						
Not re	Not regulated as a dangerous good						
14.6 Spec	14.6 Special precautions for user						
Rema	arks	: Not classified a regulations.	s dangerous in the meaning of transport				
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.							

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	 Conditions of restriction for the following entries should be considered: aluminium powder (stabilised) (Number on list 40) Phosphoric acid, C11-14-isoalkyl esters, C13-rich (Number on list 3)

according to Regulation (EC) No. 1907/2006



HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

GB EH40

H228 H315 H318 H411	:	Flammable solid. Causes skin irritation. Causes serious eye damage. Toxic to aquatic life with long lasting effects.		
Full text of other abbreviations				
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Eye Dam.	:	Serious eye damage		
Flam. Sol.	:	Flammable solids		
Skin Irrit.	:	Skin irritation		

GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period) ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

UK. EH40 WEL - Workplace Exposure Limits





HYDRO PELLET 3500

Version	Revision Date:	SDS Number:	Print Date: 06.04.2022
3.0	05.04.2022	102000029889	Date of first issue: 06.08.2018

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN