according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

Version Revision Date: SDS Number: Print Date: 25.02.2022

2.0 04.12.2019 102000000295 Date of first issue: 14.02.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA UV CHROMAL X/H Aluminium Paste

Product code : 055223G60

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS

: msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Short-term (acute) aquatic hazard, H400: Very toxic to aquatic life.

Category 1

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

*

Signal word : Warning

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

Hazard statements : H410 Very toxic to aquatic life with long lasting

effects.

Precautionary statements : **Prevention:**

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	REGULATION (EC)	(% w/w)
	Index-No.	No 1272/2008	
	Registration number		
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 50 - <= 100
	231-072-3		
	01-2119529243-45		
fatty alcohols	Not Assigned	Aquatic Acute 1;	>= 25 - < 50
		H400	
		Aquatic Chronic 2;	
		H411	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Do not leave the victim unattended.

No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand

Special powder against metal fire

Unsuitable extinguishing

media

Water Foam

ABC powder

Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Use personal protective equipment. Remove all sources of ignition.

Avoid dust formation.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Do not flush with water.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition.

Avoid dust formation.

Ensure adequate ventilation.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

use. Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on storage conditions

Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

Never allow product to get in contact with water during

storage.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	4 mg/m3	GB EH40
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is			

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

TWA (Respirable 4 mg/m3 GB EH40 dust)

Further information

For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder	Workers	Inhalation	Long-term local	3.72 mg/m3

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

(stabilised)			effects	
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer

concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the

danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective

gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water

courses or the soil.

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

Version Revision Date: SDS Number: Print Date: 25.02.2022

2.0 04.12.2019 102000000295 Date of first issue: 14.02.2014

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Pasty solid

Colour : silver

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 120 °C

Evaporation rate : No data available

Flammability (solid, gas) : Combustible Solids

Self-ignition : not auto-flammable

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower

flammability limit

: No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Bulk density : No data available

Water solubility : No data available

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.

No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

Contact with water or humid : This information is not available.

air

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

Version Revision Date: SDS Number: Print Date: 25.02.2022

2.0 04.12.2019 102000000295 Date of first issue: 14.02.2014

Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

fatty alcohols:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

Very toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

containing hazardous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company. In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

 ADR
 : UN 3077

 IMDG
 : UN 3077

 IATA
 : UN 3077

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(C13-C16 Isoalcohols)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(C13-C16 Isoalcohols)

IATA : Environmentally hazardous substance, solid, n.o.s.

(C13-C16 Isoalcohols)

14.3 Transport hazard class(es)

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

Labels : 9

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 956

aircraft)

Packing instruction (LQ) : Y956
Packing group : III

Labels : Class 9 - Miscellaneous dangerous substances and articles

IATA (Passenger)

Packing instruction : 956

(passenger aircraft)

Packing instruction (LQ) : Y956 Packing group : III

Labels : Class 9 - Miscellaneous dangerous substances and articles

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

Remarks : For single packagings <=5L / 5 kg, or combination

packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197

IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High : Not applicable

Concern for Authorisation (Article 59).

15.2 Chemical safety assessment

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid. H400 : Very toxic to aquatic life.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Flam. Sol. : Flammable solids

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

according to Regulation (EC) No. 1907/2006



STAPA UV CHROMAL X/H Aluminium Paste

 Version
 Revision Date:
 SDS Number:
 Print Date:
 25.02.2022

 2.0
 04.12.2019
 102000000295
 Date of first issue: 14.02.2014

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN