

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : METALURE LIQUID BLACK
Material number : 053377QR0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number**NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification**GHS Classification**

: Flammable liquids, Category 2, H225
Specific target organ toxicity - single exposure, Category 3,
Central nervous system, H336

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

GHS-Labeling

Symbol(s)



Signal word

: Danger

Hazard statements

: H225: Highly flammable liquid and vapour.
H336: May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.
P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
1-methoxypropan-2-ol	107-98-2
ethyl acetate	141-78-6

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
1-methoxy-2-propanol	107-98-2 203-539-1	Flam. Liq.;3;H226 STOT SE;3;H336	50 - 100
chromium	7440-47-3 231-157-5	Acute Tox.;5;H333 Aquatic Chronic;4;H413	2,5 - 10
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 ;2A;H319 STOT SE;3;H336	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.


4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Page 4 / 21	102000000649	A member of  ALTANA
-------------	--------------	---

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

This information is not available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

carefully resealed and kept upright to prevent leakage.
Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 568 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skin Indicative			
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m ³	2000-06-16	2000/39/EC
Further information		Identifies the possibility of significant uptake through the skin Indicative			
1-methoxy-2-propanol	107-98-2	AGW	100 ppm 370 mg/m ³	2010-08-04	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European			

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

		Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
chromium	7440-47-3	TWA	2 mg/m3	2006-02-09	2006/15/EC
Further information		Indicative			
chromium	7440-47-3	AGW (Inhalable fraction)	2 mg/m3	2007-12-27	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		European Union (The EU has established a limit value: deviations in value and peak limit are possible)The threshold value is based on the element content of the corresponding metal.			
chromium	7440-47-3	TWA	2 mg/m3	2006-02-09	2006/15/EC
Further information		Indicative			
chromium	7440-47-3	AGW (Inhalable fraction)	2 mg/m3	2018-06-07	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		European Union (The EU has established a limit value: deviations in value and peak limit are possible)The threshold value is based on the element content of the corresponding metal.			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m3	2017-06-08	DE TRGS 900
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm	2017-02-01	2017/164/EU

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

			1 468 mg/m3		
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m3	2017-02-01	2017/164/EU
Further information		Indicative			
chromium (III) oxide	1308-38-9	AGW (Inhalable fraction)	2 mg/m3	2018-06-07	DE TRGS 900
Peak-limit: excursion factor (category)		1;(I)			
Further information		European Union (The EU has established a limit value: deviations in value and peak limit are possible)The threshold value is based on the element content of the corresponding metal.			
chromium (III) oxide	1308-38-9	TWA	2 mg/m3	2006-02-09	2006/15/EC
Further information		Indicative			

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
1-methoxy-2-propanol	107-98-2	TWA	50 ppm	2014-03-01	
1-methoxy-2-propanol	107-98-2	STEL	100 ppm	2014-03-01	
1-methoxy-2-propanol	107-98-2	ST	150 ppm 540 mg/m3	2013-10-08	
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 360 mg/m3	2013-10-08	
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 360 mg/m3	1989-01-19	
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 540 mg/m3	1989-01-19	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

1-methoxy-2-propanol	107-98-2	PEL	100 ppm 360 mg/m3	2014-11-26	
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 540 mg/m3	2014-11-26	
chromium	7440-47-3	TWA	0,5 mg/m3	2013-10-08	
chromium	7440-47-3	TWA	0,5 mg/m3	2007-01-01	
chromium	7440-47-3	TWA	1 mg/m3	1989-01-19	
chromium	7440-47-3	TWA	0,5 mg/m3	2007-01-01	
chromium	7440-47-3	TWA	1 mg/m3	1989-01-19	
chromium	7440-47-3	TWA	0,5 mg/m3	2013-10-08	
chromium	7440-47-3	TWA	1 mg/m3	2011-07-01	
chromium	7440-47-3	PEL	0,5 mg/m3	2014-11-26	
chromium	7440-47-3	TWA	0,5 mg/m3	2007-01-01	
chromium	7440-47-3	TWA	0,5 mg/m3	2019-03-05	
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m3	2013-10-08	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m3	1997-08-04	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m3	1989-01-19	
ethyl acetate	141-78-6	PEL	400 ppm 1 400 mg/m3	2014-11-26	

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

chromium (III) oxide	1308-38-9	TWA	0,5 mg/m3	2007-01-01	
chromium (III) oxide	1308-38-9	TWA	0,5 mg/m3	2013-10-08	
chromium (III) oxide	1308-38-9	PEL	0,5 mg/m3	2014-11-26	

8.2 Exposure controls**Personal protective equipment**

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: black
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 76 °C
Flash point	: 17 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0,99 - 1,1 g/cm ³
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.


10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Page 13 / 21	102000000649	A member of  ALTANA
--------------	--------------	---

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

Acute toxicity**Components:****1-methoxy-2-propanol :**

Acute oral toxicity : LD50 Rat: 4 016 mg/kg

Acute inhalation toxicity : LC50 Rat: > 25,8 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 2 000 mg/kg

chromium :

Acute oral toxicity : LD50 Oral : > 5 000 mg/kg

Acute inhalation toxicity : LC50 : > 5,41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

ethyl acetate :

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 18 000 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

No data available

Aspiration toxicity

No data available

Further information**Product**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.,
Concentrations substantially above the TLV value may cause narcotic effects., Solvents may
degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****chromium (7440-47-3) :****Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

ethyl acetate (141-78-6) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**Additional ecological : No data available
information

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

ADR : 1263
TDG : 1263
CFR : 1263
IMDG : 1263
IATA : 1263

14.2 Proper shipping name

ADR : PAINT
TDG : PAINT
CFR : PAINT
IMDG : PAINT Classified according to 2.3.2.2 IMDG-Code
IATA : PAINT classified according to 3.3.3.1 IATA-DGR

14.3 Transport hazard class

ADR : 3
TDG : 3
CFR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packaging group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
TDG
Packaging group : III

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

Labels : 3

CFR

Packaging group : III

Labels : 3

IMDG

Packaging group : III

Labels : 3

EmS Number : F-E, S-E

IATAPacking instruction (cargo
aircraft) : 366Packing instruction
(passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packaging group : III

Labels : 3

14.5 Environmental hazards**14.6 Special precautions for user****14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Banned and/or restricted (1-methoxy-2-propanol) (chromium) (ethyl acetate)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H319	: Causes serious eye irritation.
H333	: May be harmful if inhaled.
H336	: May cause drowsiness or dizziness.
H413	: May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

METALURE LIQUID BLACK

Version 4.0

Revision Date 30.05.2022

Print Date 31.05.2022

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.