

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : METALURE CHROME Black  
Product code : 024525QR0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink Colouring agents, dyes

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
  
Telephone : +499152770  
Telefax : +499152777008  
  
E-mail address of person responsible for the SDS : [msds.eckart@altana.com](mailto:msds.eckart@altana.com)

#### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)  
Call and response in your language is possible.  
Contract no.: ECKART29003-NCEC.

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H225      Highly flammable liquid and vapour. H319      Causes serious eye irritation. H336      May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066      Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233      Keep container tightly closed. P261      Avoid breathing mist or vapours. P280      Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

n-butyl acetate  
ethyl acetate  
acetone

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	ClassificationREGUL ATION (EC) No 1272/2008	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version  
5.1

Revision Date:  
03.04.2024

SDS Number:  
102000031328

Print Date: 05.04.2024  
Date of first issue: 04.03.2019

	607-025-00-1	(Central nervous system) EUH066	
ethyl acetate	141-78-6 205-500-4 607-022-00-5  01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 50
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1  01-2119529243-45	Flam. Sol. 1; H228	>= 1 - < 10
acetone	67-64-1 200-662-2 606-001-00-8  01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version	Revision Date:	SDS Number:	Print Date: 05.04.2024
5.1	03.04.2024	102000031328	Date of first issue: 04.03.2019

---

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version	Revision Date:	SDS Number:	Print Date: 05.04.2024
5.1	03.04.2024	102000031328	Date of first issue: 04.03.2019

---

### 6.2 Environmental precautions

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
	Further information: Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	GB EH40
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
	Further information: Indicative			
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	GB EH40
		STEL	7 mg/m <sup>3</sup>	GB EH40
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
 Date of first issue: 04.03.2019

	<p>levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
	TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40	
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p>			
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
	<p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m<sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m<sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain</p>			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version  
5.1

Revision Date:  
03.04.2024

SDS Number:  
102000031328

Print Date: 05.04.2024  
Date of first issue: 04.03.2019

		particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (Inhalable)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
		Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (Respirable fraction)	4 mg/m <sup>3</sup>	GB EH40
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	147-14-8	TWA (Dusts and mists)	1 mg/m <sup>3</sup> (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m <sup>3</sup> (Copper)	GB EH40
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
		TWA	500 ppm	GB EH40



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version  
5.1

Revision Date:  
03.04.2024

SDS Number:  
102000031328

Print Date: 05.04.2024  
Date of first issue: 04.03.2019

			1,210 mg/m <sup>3</sup>	
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	7 mg/kg
	Workers	Dermal	Acute systemic effects	11 mg/kg
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg
	Consumers	Dermal	Acute systemic effects	6 mg/kg
ethyl acetate	Consumers	Oral	Long-term systemic effects	2 mg/kg
	Consumers	Oral	Acute systemic effects	2 mg/kg
	Workers	Inhalation	Long-term systemic effects	734 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	734 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	1468 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Dermal	Long-term local effects	63 mg/kg
	Consumers	Inhalation	Long-term systemic effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	734 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version  
5.1

Revision Date:  
03.04.2024

SDS Number:  
102000031328

Print Date: 05.04.2024  
Date of first issue: 04.03.2019

	Consumers	Dermal	Long-term systemic effects	37 mg/kg
	Consumers	Oral	Long-term systemic effects	4.5 mg/kg
Carbon black	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	0.06 mg/m <sup>3</sup>
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3.72 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1210 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	186 mg/kg
	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Consumers	Oral	Long-term systemic effects	62 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Intermittent water release	0.36 mg/l
	STP	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.0981 mg/kg
	Soil	0.0903 mg/kg
	ethyl acetate	Fresh water
Marine water		0.024 mg/l
STP		650 mg/l
Fresh water sediment		1.15 mg/kg
Marine sediment		0.115 mg/kg
	Soil	0.148 mg/kg
	periodical release	1.65 mg/l
	Secondary Poisoning	200 mg/kg
Carbon black	Fresh water	1 - 50 mg/l
	Marine water	0.1 mg/l
	Intermittent Release	10 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg
	STP	100 mg/l
	Soil	29.5 mg/kg
	periodical release	21 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

- Eye/face protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Form : liquid
- Colour : black
- Odour : characteristic
- Odour Threshold : No data available
- Freezing point : No data available
- Boiling point/boiling range : 77 °C
- Flammability : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : -4 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Vapor Pressure for Components:

n-butyl acetate : 10.7 hPa (20 °C)

ethyl acetate : 98.4 hPa (20 °C)

acetone : 240 hPa (20 °C)

Relative density : No data available

Density : 0.9 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle Size Distribution : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version	Revision Date:	SDS Number:	Print Date: 05.04.2024
5.1	03.04.2024	102000031328	Date of first issue: 04.03.2019

---

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

##### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg  
(Mouse): 3,000 mg/kg  
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Product:

Remarks : May cause skin irritation in susceptible persons.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

### Components:

#### **acetone:**

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Product:

Remarks : May cause irreversible eye damage.

### Components:

#### **ethyl acetate:**

Result : Eye irritation

#### **acetone:**

Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

### Components:

#### **ethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **acetone:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **ethyl acetate:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

##### **acetone:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

### SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1210  
IMDG : UN 1210  
IATA : UN 1210

#### 14.2 UN proper shipping name

ADR : PRINTING INK  
IMDG : PRINTING INK  
IATA : Printing ink

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

ADR  
Packing group : II  
Classification Code : F1

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-D

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : 3

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
n-butyl acetate (Number on list 40, 3)  
ethyl acetate (Number on list 3)

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

aluminium powder (stabilised)  
(Number on list 40)  
acetone (Number on list 3)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable  
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone  
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable  
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

### 15.2 Chemical safety assessment

No data available

---

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H228 : Flammable solid.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2017/164/EU / STEL : Short term exposure limit  
2017/164/EU / TWA : Limit Value - eight hours  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## METALURE CHROME Black

Version 5.1      Revision Date: 03.04.2024      SDS Number: 102000031328      Print Date: 05.04.2024  
Date of first issue: 04.03.2019

---

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN