according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : KU F 150 Copper Powder

Product code : 010353VZ0M1

Substance name : Sammelspez für coated copper flakes nicht Biozidprodukte

nicht entzündbar

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Colouring agents, pigments

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person

responsible for the SDS

: msds.eckart@altana.com

### 1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)

Call and response in your language is possible.

Contract no.: ECKART29003-NCEC.

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Acute toxicity, Category 3 H331: Toxic if inhaled.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Short-term (acute) aquatic hazard,

Category 1

H400: Very toxic to aquatic life.



according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

Long-term (chronic) aquatic hazard, H410: Very toxic to aquatic life with long lasting

Category 1 effects.

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H410 Very toxic to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Response:

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

#### 2.3 Other hazards

Combustible Solids

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Substance name : Sammelspez für coated copper flakes nicht Biozidprodukte

nicht entzündbar

### Components

Chem	ical name	CAS-No.	Concentration (%	M-Factor, SCL, ATE
		EC-No.Index-No.	w/w)	
		Registration number	,	
coppe	r flakes (coated with	Not Assigned	>= 50 - <= 100	M-Factor (Acute

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

 Version
 Revision Date:
 SDS Number:
 Print Date: 09.02.2023

 7.0
 07.02.2023
 102000000435
 Date of first issue: 09.01.2014

aliphatic acid)	029-019-01-X 01-2119480154-42	aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 Acute toxicity estimate
		Acute oral toxicity: 500 mg/kg Acute inhalation toxicity (dust/mist): 0.733 mg/l

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Harmful if swallowed.

Causes serious eye irritation.

Toxic if inhaled.

### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Special powder against metal fire

Dry sand ABC powder

Unsuitable extinguishing

media

Water

High volume water jet Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessarv.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Evacuate personnel to safe areas. Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water

courses or the soil.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid creating dust.

Routine housekeeping should be instituted to ensure that

dusts do not accumulate on surfaces.

Avoid formation of respirable particles.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : General industrial hygiene practice. Do not smoke. Wash

hands before breaks and at the end of workday. Keep away from food and drink. Keep away from tobacco products.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Electrical installations / working materials must comply with

the technological safety standards.

Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product

quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

102000000435 Date of first issue: 09.01.2014 7.0 07.02.2023

> place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the

technological safety standards.

Further information on

storage conditions

Protect from humidity and water.

Keep away from oxidizing agents, strongly alkaline and Advice on common storage

> strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

**Dampness** Keep in a dry, cool and well-ventilated place.

Further information on

storage stability

Keep in a dry place.

No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
copper flakes (coated with aliphatic acid)	7440-50-8	TWA (Fumes)	0.2 mg/m3 (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m3 (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m3 (Copper)	GB EH40

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
copper flakes (coated with aliphatic acid)	Workers	Inhalation	Acute systemic effects	9 mg/m3
	Workers	Skin contact	Long-term systemic effects	137 mg/kg
	Workers	Skin contact	Acute systemic effects	273 mg/kg
	Consumers	Inhalation	Long-term local effects	1 mg/m3
	Consumers	Inhalation	Acute local effects	1 mg/m3
	Consumers	Skin contact	Long-term systemic effects	137 mg/kg
	Consumers	Skin contact	Acute systemic effects	273 mg/kg

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

 Version
 Revision Date:
 SDS Number:
 Print Date: 09.02.2023

 7.0
 07.02.2023
 102000000435
 Date of first issue: 09.01.2014

Consumers	Ingestion	Long-term systemic	0.041 mg/kg
		effects	

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
copper flakes (coated with	Fresh water	0.0078 mg/l
aliphatic acid)		
	Marine water	0.0052 mg/l
	STP	0.230 mg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg

#### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : Leather

Remarks : Leather gloves The choice of an appropriate glove does not

only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Recommended

producer and this has to be observed. Recommended

preventive skin protection

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Dust impervious protective suit

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

Respirator with a dust filter

P1 filter

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

Physical state : powder

Colour : copper

Odour : odourless

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 2,597 °C

Flammability : Combustible Solids

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

Auto-ignition temperature : Not relevant

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Relative density : No data available

Density : No data available

Relative vapour density : No data available

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No hazards to be specially mentioned.

No decomposition if stored and applied as directed.

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : No data available

No data available

#### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

This information is not available.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Harmful if swallowed. Toxic if inhaled.

#### **Components:**

### copper flakes (coated with aliphatic acid):

Acute oral toxicity : LD50 Oral (Rat, male and female): 300 - 500 mg/kg

Method: OECD Test Guideline 423

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute toxicity estimate: 500 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0.733 mg/l

Test atmosphere: dust/mist

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LC50 (Rat, male): 0.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : May cause skin irritation in susceptible persons.

### Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Remarks : May cause irreversible eye damage.

### **Components:**

### copper flakes (coated with aliphatic acid):

Result : Eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Further information**

**Product:** 

Remarks : No data available

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:**

### copper flakes (coated with aliphatic acid):

M-Factor (Short-term (acute) : 10

aquatic hazard)

M-Factor (Long-term : 10

(chronic) aquatic hazard)

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

No data available

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

#### 12.7 Other adverse effects

**Product:** 

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles

European Waste Catalogue : 10 03 21 - other particulates and dust (including ball-mill dust)

containing hazardous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

 ADR
 : UN 3077

 IMDG
 : UN 3077

 IATA
 : UN 3077

14.2 UN proper shipping name

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder)

IATA : Environmentally hazardous substance, solid, n.o.s.

(Copper metal powder)

14.3 Transport hazard class(es)

Class Subsidiary risks

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

### 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

**IMDG** 

Packing group : III Labels : 9

EmS Code : F-A, S-F

Remarks : IMDG Code segregation group 7 - Heavy metals and their

salts

956

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y956
Packing group : III
Labels : 9

IATA (Passenger)

Packing instruction : 956

(passenger aircraft)

Packing instruction (LQ) : Y956
Packing group : III
Labels : 9

#### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

14.6 Special precautions for user

Remarks : For single packagings <=5L / 5 kg, or combination

packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197

IATA-DGR may be applied.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: Not applicable

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

### 15.2 Chemical safety assessment

No data available

### **SECTION 16: Other information**

#### Full text of other abbreviations

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test

according to Regulation (EC) No. 1907/2006



## **KU F 150 Copper Powder**

Version Revision Date: SDS Number: Print Date: 09.02.2023

7.0 07.02.2023 102000000435 Date of first issue: 09.01.2014

population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN