according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 05.01.2023
5.0	04.01.2023	102000000281	Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	STANDART Pyro UZ Aluminium Powder
Product code	:	047103F50
Substance name	:	aluminium powder (stabilised)
EC-No.	:	231-072-3
Index-No.	:	013-002-00-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Colouring agents, pigments
Substance/Mixture		

1.3 Details of the supplier of the safety data sheet

Company	:	ECKART GmbH Guentersthal 4 91235 Hartenstein
Telephone	:	+499152770
Telefax	:	+499152777008
E-mail address of person responsible for the SDS	:	msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe) Call and response in your language is possible. Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1 H228: Flammable solid.

Information concerning particular hazards for human and environment:

Please refer to our website for further important safety instructions for handling aluminium powder:

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 05.01.2023
5.0	04.01.2023	10200000281	Date of first issue: 02.01.2014

http://www.eckart.net/fileadmin/eckart/Service/GDA_Alupulver_Safety_engl.pdf

2.2 Label elements

Labelling (REGULATION (EC)	No 1272/2008)	
Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H228	Flammable solid.
Precautionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P240	Ground and bond container and receiving equipment.
		P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
		Response:	
		P370 + P378	In case of fire: Use for extinction: Special powder for metal fires.
		P370 + P378	In case of fire: Use for extinction: Dry sand.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1	Substances
-----	------------

Substance name	: aluminium powder (stabil	ised)
Index-No.	: 013-002-00-1	
EC-No.	: 231-072-3	
Chemical nature	: Pigment	

Components

Chemical name	CAS-No.	Concentration (%	M-Factor, SCL, ATE

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Vers 5.0	sion	Revision Date: 04.01.2023	SDS Number: 102000000281	Print Date: 05.01.20 Date of first issue: 0	
			EC-No.Index-No.	w/w)	
			Registration number		
	alumir	nium powder	7429-90-5	>= 50 - <= 100	
	(stabil	ised)	231-072-3		
	-		013-002-00-1		
			01-2119529243-45		

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move the victim to fresh air.
		Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Remove to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	Wash off immediately with soap and plenty of water.
		If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Dry sand Special powder against metal fire
Unsuitable extinguishing media	:	ABC powder Carbon dioxide (CO2)

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023		DS Number: 2000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014		
			Water Foam			
			High volume wate	er jet		
5.2 Special hazards arising from the substance or mixture						
Specific hazards during firefighting		:	Contact with wate (hydrogen).	r liberates extremely flammable gas		
5.3 Advice for firefighters						
Special protective equipment for firefighters		:	Wear self-contain necessary.	ed breathing apparatus for firefighting if		
Furthe	r information	:	separately in clos Use extinguishing circumstances an	s in case of fire, cans should be stored ed containments. I measures that are appropriate to local d the surrounding environment. y to cool fully closed containers.		

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	ive equipment and emergency procedures				
Personal precautions	 Use personal protective equipment. Evacuate personnel to safe areas. Avoid dust formation. Remove all sources of ignition. 				
6.2 Environmental precautions					
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.				
	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.				
6.3 Methods and material for containment and cleaning up					
Methods for cleaning up	: Use mechanical handling equipment. Do not use a vacuum cleaner.				

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

VersionRevision Date:SDS Number:Print Date: 05.01.20235.004.01.202310200000281Date of first issue: 02.01.2014	
---	--

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage			
7.1 Precautions for safe handling			
Advice on safe handling :	Avoid creating dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Store away from heat.		
	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.		
Advice on protection against : fire and explosion	Use explosion-proof equipment. During processing, dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge. When transferring from one container to another apply earthing measures and use conductive hose material.		
	Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.		
Hygiene measures :	Wash hands before breaks and at the end of workday.		
7.2 Conditions for safe storage, incl	luding any incompatibilities		
Requirements for storage : areas and containers	Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.		
	No smoking. Keep container tightly closed in a dry and well- ventilated place. Electrical installations / working materials must comply with the technological safety standards.		
Further information on : storage conditions	Protect from humidity and water.		
Advice on common storage :	Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and		

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 05.01.2023
5.0	04.01.2023	102000000281	Date of first issue: 02.01.2014
		strongly acid m	naterials in order to avoid exothermic reactions.
	er information on	: Keep in a dry p	lace.
	ge stability	No decomposit	ion if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m3	GB EH40
		TWA (Respirable fraction)	4 mg/m3	GB EH40
		TWA (inhalable dust)	10 mg/m3	GB EH40
	inhalable dust when samplin MDHS14/4 Ge respirable, the substance has concentration inhalable dust any dust will b levels. Some must comply of particles of a particular part response that distinguishes and 'respirable material that e available for c to the fraction definitions and contain compo-	are those fractions g is undertaken in ac eneral methods for s pracic and inhalable zardous to health ind in air equal to or greater or 4 mg.m-3 8-hour be subject to COSHF dusts have been as with the appropriate wide range of sizes. icle after entry into the it elicits, depend on two size fractions for e'., Inhalable dust appendent that penetrates to the deposition in the resp that penetrates to the dexplanatory material onents that have the nplied with., Where response	ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defin cludes dust of any kind when eater than 10 mg.m-3 8-hour TWA of respirable dust. This if people are exposed to du signed specific WELs and ex- limits., Most industrial dusts The behaviour, deposition and the nature and size of the par- the nature and size of the par- timit-setting purposes terme proximates to the fraction of mouth during breathing and biratory tract. Respirable dust and are given in MDHS14/4., Wir own assigned WEL, all the no specific short-term exposu- exposure limit should be use 4 mg/m3	e collected described in lysis or ition of a present at a TWA of s means that st above these posure to these contain nd fate of any a, and the body article. HSE ed 'inhalable' airborne s therefore a approximates e lung. Fuller Vhere dusts relevant limits ure limit is listed,
		dust)	5	
	inhalable dust when samplin MDHS14/4 G	are those fractions g is undertaken in a eneral methods for s	ses of these limits, respirable of airborne dust which will be ccordance with the methods ampling and gravimetric ana aerosols., The COSHH defin	e collected described in lysis or

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 05.01.2023
5.0	04.01.2023	102000000281	Date of first issue: 02.01.2014
	cond inha any level mus parti parti resp distin and mate avail to th defir cont shou	entration in air equal to able dust or 4 mg.m-3 & dust will be subject to C s. Some dusts have be t comply with the approp cles of a wide range of cular particle after entry onse that it elicits, depending respirable'., Inhalable de able for deposition in the e fraction that penetrate itions and explanatory is ain components that ha	alth includes dust of any kind when present at a or greater than 10 mg.m-3 8-hour TWA of 8-hour TWA of respirable dust. This means that OSHH if people are exposed to dust above these en assigned specific WELs and exposure to these briate limits., Most industrial dusts contain sizes. The behaviour, deposition and fate of any into the human respiratory system, and the body nd on the nature and size of the particle. HSE ons for limit-setting purposes termed 'inhalable' lust approximates to the fraction of airborne e and mouth during breathing and is therefore e respiratory tract. Respirable dust approximates es to the gas exchange region of the lung. Fuller material are given in MDHS14/4., Where dusts ve their own assigned WEL, all the relevant limits 'here no specific short-term exposure limit is listed, -term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	· · ·	0 0	· · /	
Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3.72 mg/m3
	Workers	Inhalation	Long-term local effects	3.72 mg/m3
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Face-shield	
		Tightly fitting safety goggles	
Hand protection Material Glove length	:	Leather Long sleeve gloves	
Remarks	:	Leather gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The suitability for a specific workplace should be discussed with the producers of the protective gloves.	

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023	SDS Number: 102000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014
Skin a	nd body protection		e resistant protective clothing. DIN EN EN 1149-1. Anti-static safety shoes.
			protective suit tection according to the amount and he dangerous substance at the work place.
Respir	atory protection	: Use suitable brea requires. Breathing appara P1 filter	thing protection if workplace concentration tus with filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state		powder
Colour	:	silver
Odour	:	odourless
Odour Threshold	:	No data available
Melting point/freezing point	:	660 °C
Boiling point/boiling range	:	2,467 °C
Flammability	:	The substance or mixture is a flammable solid with the category 1.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	30 g/m3
Flash point	:	No data available
Auto-ignition temperature	:	340 °C
Decomposition temperature	:	No data available
рН	:	substance/mixture is non-soluble (in water)
Viscosity, kinematic	:	No data available

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023		S Number: 2000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014
Soli	ubility(ies)			
	Water solubility	:	insoluble	
S	Solubility in other solvents	:	No data available	9
	tition coefficient: n- anol/water	:	No data available	9
Vap	our pressure	:	No data available	9
Rela	ative density	:	No data available	9
Den	sity	:	2.5 g/cm3	
Rela	ative vapour density	:	No data available	9
10.1 Rea No (ON 10: Stability and rea activity decomposition if stored an amical stability		-	
	decomposition if stored an			
	sibility of hazardous rea	ctio		ls and alkalis may release hydrogen.
Πaz	Hazardous reactions			
			-	n if stored and applied as directed.
			Dust may form e	xplosive mixture in air.
10.4 Cor	nditions to avoid			
Con	ditions to avoid	:	Heat, flames and	l sparks.
10.5 Inc	ompatible materials			
Mat	erials to avoid	:	Acids Bases Oxidizing agents Water	
10.6 Haz	ardous decomposition p	orod	ucts	

This information is not available.

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version	Revision Date:	SDS Number:	Print Date: 05.01.2023
5.0	04.01.2023	10200000281	Date of first issue: 02.01.2014

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity

: LC50 (Rat): > 888 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Components:

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023		DS Number: 2000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014
11.2 Info	ormation on other haza	ards		
Fur	ther information			
Pro	duct:			
Ren	narks	:	No data available	9
SECTIO	N 12: Ecological inf	orma	ition	
12.1 Tox	licity			
No d	data available			
	sistence and degradal data available	oility		
	accumulative potentia data available	I		
	bility in soil data available			
12.5 Res	ults of PBT and vPvB	asse	ssment	
Pro	duct:			
Ass	essment	:	to be either persi	nixture contains no components considered stent, bioaccumulative and toxic (PBT), or nd very bioaccumulative (vPvB) at levels of
	locrine disrupting pro data available	pertie	S	
12.7 Oth	er adverse effects			
Pro	duct:			
	itional ecological rmation	:	No data available	
SECTIO	N 13: Disposal cons	sider	ations	
	opean Waste Catalogue opean Waste Catalogue			rrous metal dust and particles particulates and dust (including ball-mill dust) dous substances
13.1 Wa	ste treatment methods			
Proc		:		f waste into sewer. ate ponds, waterways or ditches with container.



according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023		OS Number: 2000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014		
			Send to a licens	ed waste management company.		
Contaminated packaging		:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.			
SECTION	14: Transport inform	nat	tion			
14.1 UN n	umber or ID number					
ADR		:	UN 1309			
IMDG	ì	:	UN 1309			
ΙΑΤΑ		:	UN 1309			
14.2 UN p	roper shipping name					
ADR		:	ALUMINIUM POWDER, COATED			
IMDG	ì	:	ALUMINIUM POWDER, COATED			
ΙΑΤΑ		:	Aluminium powder, coated			
14.3 Trans	sport hazard class(es)					
			Class	Subsidiary risks		
ADR		:	4.1			
IMDG	ì	:	4.1			
ΙΑΤΑ		:	4.1			
14.4 Pack	ing group					
Class Hazaı Label	ng group ification Code rd Identification Number s el restriction code		II F3 40 4.1 (E)			
IMDG Packi Label: EmS Rema	ng group s Code	: : : :	ll 4.1 F-G, S-G	regation group 15 - Powdered metals		
Packi aircra		:	448			
Packi	ng instruction (LQ) ng group	::	Y441 II 4.1			

according to Regulation (EC) No. 1907/2006



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023		DS Number: 2000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014	
IATA (Passenger) Packing instruction (passenger aircraft) Packing instruction (LQ) Packing group Labels		:	445 Y441 II 4.1		
14.5 Env	ironmental hazards				
ADF Envi	R ironmentally hazardous	:	no		
IMDG Marine pollutant		:	no		
14.6 Special precautions for user					

The transport classification(s) provided herein are for informational purposes only, and solely

based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 40 aluminium powder (stabilised) (Number on list 40)
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
2 Chemical safety assessment		

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of other abbreviations



STANDART Pyro UZ Aluminium Powder

Version 5.0	Revision Date: 04.01.2023	SDS Number: 102000000281	Print Date: 05.01.2023 Date of first issue: 02.01.2014	
GB EH40		: UK. EH40 WEL	Workplace Exposure Limits	

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN