

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : STAPA METALLUX 214 Aluminium Paste

Material number : 057501G60M1

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH

Guentersthal 4 91235 Hartenstein

Telephone : +499152770 Telefax : +499152777008

E-mail address : msds.eckart@altana.com

Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Long-term (chronic) aquatic hazard, Category 3, H412

| Page 1 / 20 | 102000030576 | A member of C ALTANA |
|-------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

GHS-Labelling

Hazard statements : H412: Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label

Other hazards which do not result in classification

Combustible Solids

SECTION 3: Composition/information on ingredients

Substance No. :

Hazardous components

| Chemical name | CAS-No. EINECS-No. | Classification and labelling | Concentration[%] |
|--|-------------------------|--|------------------|
| aluminium powder (stabilised) | 7429-90-5 231-072-3 | Flam. Sol.;1;H228 | 50 - 100 |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha | 64742-48-9 918-481-9 | Flam. Liq.;4;H227 Asp. Tox.;1;H304 | 10 - 20 |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 918-668-5 | Flam. Liq.;3;H226 Acute Tox.;5;H303 Acute Tox.;5;H313 STOT SE;3;H335, H336 Asp. Tox.;1;H304 | 10 - 20 |

| Page 2 / 20 102000 | A member of C ALTANA |
|--------------------|-----------------------------|
|--------------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

| | | Aquatic Chronic;2;H411 | |
|--|-------------------------|---------------------------|--------|
| Fatty acids, C14-18 and C16-18-unsatd. | 67701-06-8 266-930-6 | Acute Tox.;5;H313 | 1 - 10 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Do not leave the victim unattended. Do not leave the victim unattended.

If inhaled : Remove to fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

| Page 3 / 20 A member of C ALTANA | Page 3 / 20 | 102000030576 | A member of C ALTANA |
|-----------------------------------|-------------|--------------|-----------------------------|
|-----------------------------------|-------------|--------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing

media

: Water, Foam, ABC powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and

contaminated fire extinguishing water must be disposed of in

accordance with local regulations. Use extinguishing

measures that are appropriate to local circumstances and the

surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

> Use personal protective equipment. Remove all sources of ignition.

Avoid dust formation.

102000030576 Page 4 / 20 A member of **O ALTANA**



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Pick up and arrange disposal without creating dust.

Sweep up and shovel.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust

formation. Ensure adequate ventilation.

For personal protection see section 8. Smoking, eating and

drinking should be prohibited in the application area.

Advice on protection against

fire and explosion

: Keep away from open flames, hot surfaces and sources of

ignition. Earthing of containers and apparatuses is essential.

Provide appropriate exhaust ventilation at places where dust

is formed.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

| Page 5 / 20 | 102000030576 | A member of C ALTANA |
|-------------|--------------|--|
| | | A STATE OF THE STA |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Requirements for storage areas and containers

: Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions

: Protect from humidity and water. Do not allow to dry.

Advice on common storage

: Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

reactions.

No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|-------------------------------------|-----------|-------------------------------------|--------------------|------------|-------------|
| aluminium powder (stabilised) | 7429-90-5 | AGW (Inhalable fraction) | 10 mg/m3 | 2014-04-02 | DE TRGS 900 |

| Page 6 / 20 ALTAI |
|-------------------|
|-------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

| Peak-limit: exc | | 2;(II) | | | |
|---|----------------|--|--|------------|----------------|
| aluminium powder (stabilised) | 7429-90-5 | AGW (Alveolate fraction) | 1,25 mg/m3 | 2014-04-02 | DE TRGS 900 |
| Peak-limit: exc factor (categor | | 2;(II) | | | |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha Peak-limit: exc factor (categor | | AGW | 300 mg/m3 | 2017-11-30 | DE TRGS 900 |
| Further informa | - | | limit for hydrocarbo ssion for dangerous) | | e also No. 2.9 |
| Solvent naphtha (petroleum), light arom. | 64742-95- 6 | AGW | 100 mg/m3 | 2009-02-16 | DE TRGS 900 |
| Peak-limit: exc factor (categor | | 2;(II) | | | |
| Further informa | ation | Group exposure limit for hydrocarbon solvent mixturesCommission for dangerous substancesSee also No. 2.9 of the TRGS 900 | | | |

United States of America (USA):

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Update | Basis |
|-------------------------------------|-----------|-------------------------------------|-------------------------------------|------------|-------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust) | 50 Million particles per cubic foot | 2012-07-01 | |
| aluminium | 7429-90-5 | TWA | 5 mg/m3 | 2013-10-08 | |

| A member of C ALIANA | Page 7 / 20 | 102000030576 | A member of C ALTANA |
|----------------------|-------------|--------------|-----------------------------|
|----------------------|-------------|--------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

| powder (stabilised) | | (Respirable) | | |
|-------------------------------------|-----------|--|-------------------------------------|------------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust) | 15 mg/m3 | 2012-07-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total) | 10 mg/m3 | 2013-10-08 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction) | 5 mg/m3 | 2012-07-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction) | 15 Million particles per cubic foot | 2012-07-01 |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Total dust) | 10 mg/m3 | 2014-11-26 |
| aluminium powder (stabilised) | 7429-90-5 | PEL (respirable dust fraction) | 5 mg/m3 | 2014-11-26 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m3 | 2008-01-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA | 5 mg/m3 | 2005-09-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Total) | 15 mg/m3 | 1989-01-19 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable fraction) | 5 mg/m3 | 1989-01-19 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (total dust) | 15 mg/m3 | 2011-07-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable fraction) | 5 mg/m3 | 2011-07-01 |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

| aluminium powder (stabilised) | 7429-90-5 | TWA (Total dust) | 15 mg/m3 | 1989-01-19 |
|-------------------------------------|-----------|--|----------|------------|
| aluminium powder (stabilised) | 7429-90-5 | TWA (respirable dust fraction) | 5 mg/m3 | 1989-01-19 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (welding fumes) | 5 mg/m3 | 2013-10-08 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (pyro powders) | 5 mg/m3 | 2013-10-08 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Respirable particulate matter) | 1 mg/m3 | 2013-03-01 |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Fumes) | 5 mg/m3 | 1989-01-19 |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Welding fumes) | 5 mg/m3 | 2017-10-02 |
| aluminium powder (stabilised) | 7429-90-5 | PEL (Pyro powders) | 5 mg/m3 | 2017-10-02 |

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special

workplace conditions (mechanical strain, duration of contact).

The exact break through time can be obtained from the

| Page 9 / 20 | 102000030576 | A member of C ALTANA |
|-------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

: Protective suit

Respiratory protection : Use suitable breathing protection if workplace concentration

requires.

: No personal respiratory protective equipment normally

required.

Environmental exposure controls

General advice

Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Water : The product should not be allowed to enter drains, water

courses or the soil.

:

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Page 10 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|--|
| | | to the state of th |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Appearance : Pasty solid

Colour : silver

Odour : characteristic

pH : substance/mixture is non-soluble (in water)

Freezing point : No data available
Boiling point/boiling range : No data available
Flash point : No data available
Bulk density : No data available
Flammability (solid, gas) : Combustible Solids

Auto-flammability : not auto-flammable
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Density : 1,3 - 2,0 g/cm3

Solubility(ies)

Water solubility : insoluble

Miscibility with water : immiscible

Solubility in other solvents No data available Partition coefficient: n-octanol/water No data available Ignition temperature : No data available Thermal decomposition No data available Viscosity, dynamic No data available Viscosity, kinematic : No data available Flow time No data available Explosive properties Not explosive

| Page 11 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.

Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of

hydrogen.

Vapour/air-mixtures are explosive at intense warming.

Stable under recommended storage conditions., No hazards

to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Do not allow to dry.
No data available

10.5 Incompatible materials

Materials to avoid : Acids

Bases

Oxidizing agents

Highly halogenated compounds

10.6 Hazardous decomposition products

Hazardous decomposition : No data available

products

| Page 12 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Other information : No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

Acute inhalation toxicity : LC50 Rat: Test atmosphere: vapour

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Solvent naphtha (petroleum), light arom. :

Acute oral toxicity : LD50 Rat: 3 492 mg/kg

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Fatty acids, C14-18 and C16-18-unsatd.:

Acute oral toxicity : LD50 Rat: > 5 000 mg/kg

| Page 13 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Acute inhalation toxicity : LC50 Rat: > 46 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Rabbit: > 3 160 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

| e 14 / 20 102000030576 | A member of C ALTANA |
|--------------------------------------|-----------------------------|
|--------------------------------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Solvent naphtha (petroleum), light arom. (64742-95-6):

Ecotoxicology Assessment

Long-term (chronic) aquatic : Toxic to aquatic life with long lasting effects.

hazard

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

| 15 / 20 102000030576 | A member of C ALTANA |
|-----------------------------|-----------------------------|
|-----------------------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

SECTION 14: Transport information

14.1 UN number

ADR

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

| Page 16 / 20 ALT/ | 102000030576 A member of () ALTANA | 102000030576 | Page 16 / 20 |
|-------------------|---|--------------|--------------|
|-------------------|---|--------------|--------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Not dangerous goods

IATA

Not dangerous goods

14.2 Proper shipping name

ADR

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.3 Transport hazard class

ADR

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.4 Packing group

ADR

| 2 17 / 20 | 102000030576 | A member of C ALTANA |
|-----------|--------------|-----------------------------|
|-----------|--------------|-----------------------------|



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

Not dangerous goods

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.5 Environmental hazards

14.6 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

: Not applicable

: Not applicable: Not applicable

| Page 18 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|-----------------------------|
| | 1 | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Banned and/or restricted (aluminium powder (stabilised)) (Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha) (Solvent naphtha (petroleum), light arom.)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H227 : Combustible liquid.
H228 : Flammable solid.
H303 : May be harmful if swallowed.
H304 : May be fatal if availaged and a

H304 : May be fatal if swallowed and enters airways.

H313
H335
May be harmful in contact with skin.
H336
May cause respiratory irritation.
H336
May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

| Page 19 / 20 | 102000030576 | A member of C ALTANA |
|--------------|--------------|-----------------------------|
| | | |



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

STAPA METALLUX 214 Aluminium Paste

Version 2.2 Revision Date 13.05.2022 Print Date 17.10.2023