

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : PLATINVARIO AE-82002  
Material number : 053175JD0

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Flammable solids, Category 1, H228  
Serious eye damage/eye irritation, Category 2A, H319  
Specific target organ toxicity - single exposure, Category 3,

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Central nervous system, H336

**GHS-Labelling**

Symbol(s)

:



Signal word

:

Danger

Hazard statements

:

H228: Flammable solid.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

Precautionary statements

:

**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P261 Avoid breathing dust.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P317 If eye irritation persists: Get medical help.  
P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.  
P370 + P378 In case of fire: Use for extinction: Dry sand.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Hazardous components which must be listed on the label**Identification  
ethyl acetateCAS-No.  
141-78-6**SECTION 3: Composition/information on ingredients**

Substance No. :

**Hazardous components**

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 ;2A;H319 STOT SE;3;H336	50 - 100
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 20

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

General advice : Move the victim to fresh air.

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

	Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: Wash off immediately with soap and plenty of water.  If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water.  Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Dry sand, Special powder against metal fire

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Unsuitable extinguishing media : Water, Foam, Carbon dioxide (CO<sub>2</sub>), ABC powder

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Contact with water liberates extremely flammable gas (hydrogen).

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

**6.2 Environmental precautions**

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Keep away from heat and sources of ignition. Avoid dust  
formation. Ensure adequate ventilation.

Avoid formation of respirable particles. Do not breathe  
vapours/dust. Avoid exposure - obtain special instructions  
before use. Avoid contact with skin and eyes. For personal  
protection see section 8. Smoking, eating and drinking should  
be prohibited in the application area. Provide sufficient air  
exchange and/or exhaust in work rooms. Dispose of rinse  
water in accordance with local and national regulations.

Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take  
measures to prevent the build up of electrostatic charge. Use  
explosion-proof equipment.

Avoid dust formation. Keep away from open flames, hot  
surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water. Do not allow to dry.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

This information is not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	AGW	200 ppm	2017-06-08	DE TRGS 900

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

			730 mg/m3		
Peak-limit: excursion factor (category)		2;(I)			
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	STEL	400 ppm 1 468 mg/m3	2017-02-01	2017/164/EU
Further information		Indicative			
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m3	2017-02-01	2017/164/EU
Further information		Indicative			
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,25 mg/m3	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

**United States of America (USA):**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m <sup>3</sup>	2013-10-08	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m <sup>3</sup>	1997-08-04	
ethyl acetate	141-78-6	TWA	400 ppm 1 400 mg/m <sup>3</sup>	1989-01-19	
ethyl acetate	141-78-6	PEL	400 ppm 1 400 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	TWA (total dust)	50 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	TWA (Respirable)	5 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2012-07-01	
aluminium	7429-90-5	TWA (total)	10 mg/m <sup>3</sup>	2013-10-08	
aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m <sup>3</sup>	2012-07-01	
aluminium	7429-90-5	TWA (respirable fraction)	15 Million particles per cubic foot	2012-07-01	
aluminium	7429-90-5	PEL (Total dust)	10 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	PEL (respirable dust fraction)	5 mg/m <sup>3</sup>	2014-11-26	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	2008-01-01	
aluminium	7429-90-5	TWA	5 mg/m <sup>3</sup>	2005-09-01	
aluminium	7429-90-5	TWA (Total)	15 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (Respirable fraction)	5 mg/m <sup>3</sup>	1989-01-19	
aluminium	7429-90-5	TWA (total dust)	15 mg/m <sup>3</sup>	2011-07-01	

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

aluminium	7429-90-5	TWA (respirable fraction)	5 mg/m3	2011-07-01	
aluminium	7429-90-5	TWA (Total dust)	15 mg/m3	1989-01-19	
aluminium	7429-90-5	TWA (respirable dust fraction)	5 mg/m3	1989-01-19	
aluminium	7429-90-5	TWA (welding fumes)	5 mg/m3	2013-10-08	
aluminium	7429-90-5	TWA (pyro powders)	5 mg/m3	2013-10-08	
aluminium	7429-90-5	TWA (Respirable particulate matter)	1 mg/m3	2013-03-01	
aluminium	7429-90-5	TWA (Fumes)	5 mg/m3	1989-01-19	
aluminium	7429-90-5	PEL (Welding fumes)	5 mg/m3	2017-10-02	
aluminium	7429-90-5	PEL (Pyro powders)	5 mg/m3	2017-10-02	
aluminium	7429-90-5	TWA (powder)	5 mg/m3	1989-01-19	

**8.2 Exposure controls****Personal protective equipment**

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

## Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

## Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).  
The exact break through time can be obtained from the

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

- : Long sleeved clothing  
Safety shoes
- : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

- : Use suitable breathing protection if workplace concentration requires.
- : In the case of dust or aerosol formation use respirator with an approved filter.

**Environmental exposure controls**

General advice

- : The product should not be allowed to enter drains, water courses or the soil.
- : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

If the product contaminates rivers and lakes or drains inform  
respective authorities.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: 76 °C
Flash point	: No data available
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: not auto-flammable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air.

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents.  
Contact with acids and alkalis may release hydrogen.  
Mixture reacts slowly with water resulting in evolution of hydrogen.  
Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

**10.4 Conditions to avoid**

Conditions to avoid : Do not allow to dry.  
  
Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Acids

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Bases  
Oxidizing agents  
Highly halogenated compounds

**10.6 Hazardous decomposition products**

Other information : No data available

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity****Components:****ethyl acetate :**

Acute oral toxicity : Rat: 5 620 mg/kg

Acute inhalation toxicity : LC50 Rat: 56 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Rabbit: > 18 000 mg/kg

**Skin corrosion/irritation****Product**

May cause skin irritation in susceptible persons.

# SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## PLATINVARIO AE-82002

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

### Serious eye damage/eye irritation

#### Product

Eye irritation

### Respiratory or skin sensitisation

No data available

### Carcinogenicity

No data available

### Toxicity to reproduction/fertility

No data available

### Reprod.Tox./Development/Teratogenicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****ethyl acetate (141-78-6) :**

Toxicity to daphnia and other : (Daphnia (water flea)): 717 mg/l  
aquatic invertebrates

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**

Additional ecological : No data available



**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

information

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- |                        |   |  |
|------------------------|---|--|
| Product                | : | Do not dispose of waste into sewer.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company.<br>In accordance with local and national regulations. |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum.<br>In accordance with local and national regulations.               |

**SECTION 14: Transport information****14.1 UN number**

- |      |   |      |
|------|---|------|
| ADR  | : | 1325 |
| TDG  | : | 1325 |
| CFR  | : | 1325 |
| IMDG | : | 1325 |
| IATA | : | 1325 |

**14.2 Proper shipping name**

- |     |   |  |
|-----|---|--|
| ADR | : | FLAMMABLE SOLID, ORGANIC, N.O.S.<br>(Aluminium pigment paste ) |
|-----|---|--|

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

**TDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste )

**CFR** : FLAMMABLE SOLIDS, ORGANIC, N.O.S.  
(Aluminum pigment paste )

**IMDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(,Aluminium pigment paste )

**IATA** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**14.3 Transport hazard class**

**ADR** : 4.1

**TDG** : 4.1

**CFR** : 4.1

**IMDG** : 4.1

**IATA** : 4.1

**14.4 Packing group**

**ADR**

Packaging group : II

Classification Code : F1

Hazard Identification Number : 40

Labels : 4.1

Tunnel restriction code : (E)

**TDG**

Packaging group : II

Labels : 4.1

**CFR**

Packaging group : II

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

Labels : 4.1

**IMDG**

Packaging group : II

Labels : 4.1

EmS Number : F-G, S-G

**IATA**Packing instruction (cargo  
aircraft) : 448Packing instruction  
(passenger aircraft) : 445

Packing instruction (LQ) : Y441

Packaging group : II

Labels : 4.1

**14.5 Environmental hazards****IMDG** :**14.6 Special precautions for user****IMDG Code- segregation group:**

: IMDG Code segregation group 15 - Powdered metals

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No data available

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**PLATINVARIO AE-82002**

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Banned and/or restricted (ethyl acetate) (aluminium powder (stabilised)) (Phosphoric acid polyester (72243-070628, Germany))

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H228	: Flammable solid.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

## PLATINVARIO AE-82002

Version 3.0

Revision Date 24.01.2023

Print Date 25.01.2023

---