

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : METALURE CHROME Richgold
Product code : 024504QR0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Colorant; Printing ink related material; Printing ink, Colouring agents, dyes

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770
Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

NCEC: +44 1235 239670 (Europe)
Call and response in your language is possible.
Contract no.: ECKART29003-NCEC.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | |
|--------------------------------|---|--|
| Hazard pictograms | : |   |
| Signal word | : | Danger |
| Hazard statements | : | H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Precautionary statements | : | Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

Hazardous components which must be listed on the label:

n-butyl acetate
ethyl acetate
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | ClassificationREGUL ATION (EC) No 1272/2008 | Concentration (% w/w) |
|-----------------|---|---|--------------------------|
| n-butyl acetate | 123-86-4 204-658-1 | Flam. Liq. 3; H226 STOT SE 3; H336 | >= 50 - <= 100 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version
5.3

Revision Date:
03.04.2024

SDS Number:
102000031331

Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | | |
|-------------------------------|--|---|--------------|
| | 607-025-00-1 01-2119485493-29 | (Central nervous system) EUH066 | |
| ethyl acetate | 141-78-6 205-500-4 607-022-00-5 01-2119475103-46 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066 | >= 25 - < 50 |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 013-002-00-1 01-2119529243-45 | Flam. Sol. 1; H228 | >= 1 - < 10 |
| acetone | 67-64-1 200-662-2 606-001-00-8 01-2119471330-49 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066 | >= 1 - < 10 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Move the victim to fresh air.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

Wash off immediately with soap and plenty of water.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

Immediately flush eye(s) with plenty of water.
- If swallowed : Keep respiratory tract clear.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 05.04.2024 |
| 5.3 | 03.04.2024 | 102000031331 | Date of first issue: 04.03.2019 |

Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
ABC powder
Foam

Unsuitable extinguishing media : High volume water jet
Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Evacuate personnel to safe areas.

6.2 Environmental precautions

General advice : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. The product should not be allowed to enter drains, water courses or the soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Use mechanical handling equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-----------------|---------------------------------|-------------------------------|----------------------------------|------------------|
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | TWA | 150 ppm 724 mg/m ³ | GB EH40 |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U |
| | Further information: Indicative | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version
5.3

Revision Date:
03.04.2024

SDS Number:
102000031331

Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | | | |
|---|-----------|---------------------------|------------------------------------|-------------|
| ethyl acetate | 141-78-6 | TWA | 200 ppm 734 mg/m ³ | GB EH40 |
| | | STEL | 400 ppm 1,468 mg/m ³ | GB EH40 |
| | | STEL | 400 ppm 1,468 mg/m ³ | 2017/164/EU |
| Further information: Indicative | | | | |
| | | TWA | 200 ppm 734 mg/m ³ | 2017/164/EU |
| Further information: Indicative | | | | |
| aluminium powder (stabilised) | 7429-90-5 | TWA (Inhalable) | 10 mg/m ³ | GB EH40 |
| | | TWA (Respirable fraction) | 4 mg/m ³ | GB EH40 |
| | | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| <p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.</p> | | | | |
| | | TWA (Respirable dust) | 4 mg/m ³ | GB EH40 |
| <p>Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these</p> | | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version
5.3

Revision Date:
03.04.2024

SDS Number:
102000031331

Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | | | |
|---------|---|------|--------------------------|------------|
| | must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | |
| acetone | 67-64-1 | TWA | 500 ppm 1,210 mg/m3 | 2000/39/EC |
| | Further information: Indicative | | | |
| | | TWA | 500 ppm 1,210 mg/m3 | GB EH40 |
| | | STEL | 1,500 ppm 3,620 mg/m3 | GB EH40 |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-----------------|-----------|-----------------|----------------------------|------------|
| n-butyl acetate | Workers | Inhalation | Long-term systemic effects | 48 mg/m3 |
| | Workers | Inhalation | Acute systemic effects | 600 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 300 mg/m3 |
| | Workers | Inhalation | Acute local effects | 600 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 7 mg/kg |
| | Workers | Dermal | Acute systemic effects | 11 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m3 |
| | Consumers | Inhalation | Acute systemic effects | 300 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 35.7 mg/m3 |
| | Consumers | Inhalation | Acute local effects | 300 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 3.4 mg/kg |
| | Consumers | Dermal | Acute systemic effects | 6 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 2 mg/kg |
| | Consumers | Oral | Acute systemic effects | 2 mg/kg |
| ethyl acetate | Workers | Inhalation | Long-term systemic | 734 mg/m3 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version
5.3

Revision Date:
03.04.2024

SDS Number:
102000031331

Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | | effects | |
|-------------------------------|-----------|------------|----------------------------|------------------------|
| | Workers | Inhalation | Long-term local effects | 734 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 1468 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 1468 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 63 mg/kg |
| | Workers | Dermal | Long-term local effects | 63 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 367 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 367 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 734 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 734 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 37 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 4.5 mg/kg |
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3.72 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 3.72 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 3.95 mg/kg |
| acetone | Workers | Inhalation | Long-term systemic effects | 1210 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 2420 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 1210 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 186 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 200 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 62 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 62 mg/kg |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|-----------------|----------------------------|--------------|
| n-butyl acetate | Fresh water | 0.18 mg/l |
| | Marine water | 0.018 mg/l |
| | Intermittent water release | 0.36 mg/l |
| | STP | 35.6 mg/l |
| | Fresh water sediment | 0.981 mg/kg |
| | Marine sediment | 0.0981 mg/kg |
| | Soil | 0.0903 mg/kg |
| ethyl acetate | Fresh water | 0.24 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

| | | |
|-------------------------------|----------------------|-------------|
| | Marine water | 0.024 mg/l |
| | STP | 650 mg/l |
| | Fresh water sediment | 1.15 mg/kg |
| | Marine sediment | 0.115 mg/kg |
| | Soil | 0.148 mg/kg |
| | periodical release | 1.65 mg/l |
| | Secondary Poisoning | 200 mg/kg |
| aluminium powder (stabilised) | Fresh water | 0.0749 mg/l |
| | clarification plant | 20 mg/l |
| acetone | Fresh water | 10.6 mg/l |
| | Marine water | 1.06 mg/l |
| | Fresh water sediment | 30.4 mg/kg |
| | Marine sediment | 3.04 mg/kg |
| | STP | 100 mg/l |
| | Soil | 29.5 mg/kg |
| | periodical release | 21 mg/l |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing problems.
Goggles

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

Form : liquid

Colour : gold

Odour : characteristic

Odour Threshold : No data available

Freezing point : No data available

Boiling point/boiling range : 77 °C

Flammability : No data available

Flammability (liquids) : Flammable liquids

Upper explosion limit / Upper flammability limit : Upper explosion limit 11.5 %(V)

Lower explosion limit / Lower flammability limit : Lower explosion limit 2.1 %(V)

Flash point : -4 °C

Auto-ignition temperature : 427 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Vapor Pressure for Components:

 n-butyl acetate : 10.7 hPa (20 °C)

 ethyl acetate : 98.4 hPa (20 °C)

 acetone : 240 hPa (20 °C)

Relative density : No data available

Density : 0.9 g/cm³ (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Print Date: 05.04.2024 |
| 5.3 | 03.04.2024 | 102000031331 | Date of first issue: 04.03.2019 |

Relative vapour density : No data available

Particle characteristics
Particle Size Distribution : No data available

9.2 Other information

Self-ignition : No data available

Miscibility with water : immiscible

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Contact with acids and alkalis may release hydrogen.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Do not allow evaporation to dryness.

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

This information is not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

Components:

ethyl acetate:

Acute oral toxicity : (Rat): 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 56 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 18,000 mg/kg

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

acetone:

Acute oral toxicity : LD50 (Rabbit): 4,700 - 5,800 mg/kg
(Mouse): 3,000 mg/kg
(Rat): 9,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

acetone:

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version
5.3

Revision Date:
03.04.2024

SDS Number:
102000031331

Print Date: 05.04.2024
Date of first issue: 04.03.2019

Components:

ethyl acetate:

Result : Eye irritation

acetone:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

acetone:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Further information

Product:

Remarks : Solvents may degrease the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethyl acetate:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

acetone:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 21,600 mg/l

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1210
IMDG : UN 1210
IATA : UN 1210

14.2 UN proper shipping name

ADR : PRINTING INK
IMDG : PRINTING INK
IATA : Printing ink

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADR | : 3 | |
| IMDG | : 3 | |
| IATA | : 3 | |

14.4 Packing group

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)
Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : 3

IATA (Passenger)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3
n-butyl acetate (Number on list 40, 3)
ethyl acetate (Number on list 3)
aluminium powder (stabilised) (Number on list 40)
acetone (Number on list 3)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H228 : Flammable solid.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2017/164/EU / STEL : Short term exposure limit
2017/164/EU / TWA : Limit Value - eight hours
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



METALURE CHROME Richgold

Version 5.3 Revision Date: 03.04.2024 SDS Number: 102000031331 Print Date: 05.04.2024
Date of first issue: 04.03.2019

International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|--------------|------|
| Flam. Liq. 2 | H225 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN