

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : ROTOSTAR UV/LED FPG 730 876 FLEXO INK  
Material number : 027815U11

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

This information is not available.

**1.3 Details of the supplier of the safety data sheet**

Company : ECKART GmbH  
Guntersthal 4  
91235 Hartenstein  
Telephone : +499152770  
Telefax : +499152777008  
E-mail address : msds.eckart@altana.com  
Responsible/issuing person

**1.4 Emergency telephone number****NCEC:**

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

**SECTION 2: Hazards identification****GHS Classification**

: Acute toxicity, Category 5, Oral, H303  
Skin corrosion/irritation, Category 2, H315  
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

Skin sensitisation, Category 1, H317  
 Short-term (acute) aquatic hazard, Category 1, H400  
 Long-term (chronic) aquatic hazard, Category 1, H410

### GHS-Labeling

Symbol(s)



Signal word

: Warning

Hazard statements

: H303: May be harmful if swallowed.  
 H315: Causes skin irritation.  
 H317: May cause an allergic skin reaction.  
 H319: Causes serious eye irritation.  
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
 P261 Avoid breathing mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P301 + P333 + P317 IF SWALLOWED or if skin irritation or rash occurs: Get medical help.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P317 If eye irritation persists: Get medical help.  
 P391 Collect spillage.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

### Hazardous components which must be listed on the label

Identification	CAS-No.
copper	7440-50-8
Propylidyntrimethanol, ethoxylated, esters with acrylic acid	28961-43-5
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7
Glycerol, propoxylated, esters with acrylic acid	52408-84-1
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7

### SECTION 3: Composition/information on ingredients

Substance No. :

#### Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	20 - 25
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-propen-1-yl)oxy]-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1)	51728-26-8	Skin Irrit.;2;H315 Eye Irrit.;2;H319 Aquatic Chronic;2;H411	10 - 20
Propylidyntrimethanol, ethoxylated, esters with acrylic	28961-43-5	;2A;H319 Skin Sens.;1;H317	10 - 20

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

acid			
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7	;2A;H319 Skin Sens.;1A;H317 Aquatic Chronic;3;H412	2,5 - 10
zinc	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	2,5 - 10
2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane	144086-02-2 604-394-0	;2A;H319 Aquatic Chronic;2;H411	2,5 - 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1	;2A;H319 Skin Sens.;1;H317	1 - 10
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7	Acute Tox.;5;H303 Acute Tox.;5;H313 Skin Sens.;1;H317 Aquatic Chronic;4;H413	1 - 2,5
2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-(phenylmethylene)-	7078-98-0	Skin Sens.;1;H317 Aquatic Chronic;4;H413	0,1 - 0,25
2-Propenoic acid, reaction products with pentaerythritol	1245638-61-2	Acute Tox.;4;H302 Skin Irrit.;2;H315 Eye Dam.;1;H318 Skin Sens.;1;H317 Aquatic Acute;2;H401	0,1 - 0,25

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

		Aquatic Chronic;2;H411	
Benzene, ethenyl-, copolymer with 2,5-Furandione and Benzene, 1,1'-(1,1-dimethyl-3- methylene-1,3-propanediyl)bis- ,rp. with Oxirane	Not Assigned941- 326-1	Aquatic Acute;1;H400	0,1 - 0,25

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.  
Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air.  
If unconscious, place in recovery position and seek medical  
advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If skin irritation persists, call a physician.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

This information is not available.

**4.3 Indication of any immediate medical attention and special treatment needed**

This information is not available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder

Unsuitable extinguishing media : Water, High volume water jet, Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

Ensure adequate ventilation.  
Use personal protective equipment.

**6.2 Environmental precautions**

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and materials for containment and cleaning up**

Methods for cleaning up : Use mechanical handling equipment.  
Pick up and transfer to properly labelled containers.  
Do not flush with water.  
Contain spillage, and then collect with non-combustible  
absorbent material, (e.g. sand, earth, diatomaceous earth,  
vermiculite) and place in container for disposal according to  
local / national regulations (see section 13).  
Soak up with inert absorbent material (e.g. sand, silica gel,  
acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Do not breathe vapours/dust. Avoid exposure - obtain special  
instructions before use. Avoid contact with skin and eyes. For  
personal protection see section 8. Smoking, eating and  
drinking should be prohibited in the application area. Dispose  
of rinse water in accordance with local and national  
regulations. Persons susceptible to skin sensitisation

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.


Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Page 8 / 21	102000036661	A member of 
-------------	--------------	---



**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

This information is not available.

**SECTION 8: Exposure controls/personal protection**
**8.1 Control parameters**
**Germany:**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
copper	7440-50-8	AGW (inhalable fraction)	1 mg/m <sup>3</sup>		DE TRGS 900
zinc	7440-66-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
zinc	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	2021-07-02	DE TRGS 900
Peak-limit: excursion factor (category)		2;(II)			
Further information		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

**8.2 Exposure controls**
**Personal protective equipment**

Eye protection : Safety glasses  
 : Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

Hand protection

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023


Print Date 11.10.2023

Material	:	Solvent-resistant gloves (butyl-rubber)
Remarks	:	<p>Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.</p> <p>Recommended preventive skin protection Skin should be washed after contact.</p> <p>The suitability for a specific workplace should be discussed with the producers of the protective gloves.</p>
Skin and body protection	:	<p>The suitability for a specific workplace should be discussed with the producers of the protective gloves.</p> <p>Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.</p>
Respiratory protection	:	<p>Use suitable breathing protection if workplace concentration requires.</p> <p>Equipment should conform to EN 14387</p>

**Environmental exposure controls**

General advice	:	<p>The product should not be allowed to enter drains, water courses or the soil.</p> <p>Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.</p> <p>If the product contaminates rivers and lakes or drains inform respective authorities.</p>
----------------	---	--

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**

Page 10 / 21	102000036661	A member of 
--------------	--------------	---

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

Appearance	: liquid
Colour	: gold
Odour	: characteristic
pH	: substance/mixture is non-soluble (in water)
Freezing point	: No data available
Boiling point/boiling range	: > 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1,4 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

**9.2 Other information**

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

No data available

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**Conditions to avoid : Do not allow evaporation to dryness.  
No data available**10.5 Incompatible materials**

Materials to avoid : No data available

**10.6 Hazardous decomposition products**Hazardous decomposition :  
productsOther information : Carbon monoxide, carbon dioxide and unburned  
hydrocarbons (smoke).**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

**Components:****copper :**

Acute oral toxicity : The component/mixture is moderately toxic after single  
ingestion.

**phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide :**

Acute oral toxicity : LD50 Rat: > 2 000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Rat: > 2 000 mg/kg

Method: OECD Test Guideline 402

**Skin corrosion/irritation****Product**

May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product**

May cause irreversible eye damage.

**Respiratory or skin sensitisation****Product**

Causes sensitisation.

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**Carcinogenicity**

No data available

**Toxicity to reproduction/fertility**

No data available

**Reprod.Tox./Development/Teratogenicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product**

No data available

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:**

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

**copper (7440-50-8) :**

M-Factor : 10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**2-Propenoic acid, reaction products with dipentaerythritol (1384855-91-7) :**
**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

**zinc (7440-66-6) :**
**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

**2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane (144086-02-2) :**
**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

**phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7) :**
**Ecotoxicology Assessment**

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

**Benzene, ethenyl-, copolymer with 2,5-Furandione and Benzene, 1,1'-(1,1-dimethyl-3-methylene-1,3-propanediyl)bis-,rp. with Oxirane ( ) :**
**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

**12.2 Persistence and degradability**

No data available

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

No data available

**12.6 Other adverse effects****Product:**Additional ecological  
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.



**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

**SECTION 14: Transport information****14.1 UN number****ADR** : 3082**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 3082**IATA** : 3082**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder )**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(,Copper metal powder )**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Copper metal powder)**14.3 Transport hazard class****ADR** : 9**TDG**

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG** : 9**IATA** : 9**14.4 Packing group****ADR**

Packaging group : III

Classification Code : M6

Hazard Identification Number : 90

Labels : 9

Tunnel restriction code : (-)

**TDG**

Not dangerous goods

**CFR**

Not dangerous goods

**IMDG**

Packaging group : III

Labels : 9

**IATA**Packing instruction (cargo  
aircraft) : 964Packing instruction  
(passenger aircraft) : 964

Packing instruction (LQ) : Y964

Packaging group : III

Labels : 9

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

## ROTOSTAR UV/LED FPG 730 876 FLEXO INK

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

### 14.5 Environmental hazards

**ADR** : Environmentally hazardous  
**IMDG** : Marine pollutant

### 14.6 Special precautions for user

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable  
 REACH - List of substances subject to authorisation (Annex XIV) : Not applicable  
 Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable  
 Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable  
 REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :  
 REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Banned and/or restricted (Propylidynetrimethanol, ethoxylated, esters with acrylic acid) (2-Propenoic acid, reaction products with dipentaerythritol)

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

(2-Propenoic acid, polymer with 2,2-bis(hydroxymethyl)-1,3-propanediol, methyloxirane and oxirane)  
(Glycerol, propoxylated, esters with acrylic acid)  
(2,6-bis(1,1-dimethylethyl)-4-(phenylenemethylene)cyclohexa-2,5-dien-1-one)

**15.2 Chemical safety assessment**

No data available

**SECTION 16: Other information****Full text of H-Statements**

H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H313	: May be harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H400	: Very toxic to aquatic life.
H401	: Toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

Globally Harmonized System of Classification and Labelling of  
Chemicals (GHS)

**ROTOSTAR UV/LED FPG 730 876 FLEXO INK**

Version 2.0

Revision Date 10.10.2023

Print Date 11.10.2023

---

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.