

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LITHOFLEX XA 15 01 Rich Gold
Material number : 024918BT0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Flammable solids, Category 1, H228
Acute toxicity, Category 4, Oral, H302
Serious eye damage/eye irritation, Category 2A, H319

LITHOFLEX XA 15 01 Rich Gold


Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Short-term (acute) aquatic hazard, Category 1, H400
 Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

- Symbol(s) : 
- Signal word : Danger
- Hazard statements : H228: Flammable solid.
 H302: Harmful if swallowed.
 H319: Causes serious eye irritation.
 H410: Very toxic to aquatic life with long lasting effects.
- Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P370 + P378 In case of fire: Use for extinction: Special powder for metal fires.
 P370 + P378 In case of fire: Use for extinction: Dry sand.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification CAS-No.
 copper 7440-50-8

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

SECTION 3: Composition/information on ingredients

Substance name : RG 4060 SPK

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	50 - 100
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Acute Tox.;5;H303 ;2;H315 ;1;H318 STOT RE;2;H373 Asp. Tox.;1;H304 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	0,1 - 0,25

For the full text of the H-Statements mentioned in this Section, see Section 16.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder
- Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Evacuate personnel to safe areas.
Avoid dust formation.
Avoid breathing dust.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid creating dust. Routine housekeeping should be
instituted to ensure that dusts do not accumulate on surfaces.

Avoid formation of respirable particles. Do not breathe
vapours/dust. Avoid contact with skin and eyes. For personal
protection see section 8. Smoking, eating and drinking should
be prohibited in the application area. Dispose of rinse water in
accordance with local and national regulations.

Advice on protection against : Normal measures for preventive fire protection.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

fire and explosion

Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures

: General industrial hygiene practice. Do not smoke. Wash hands before breaks and at the end of workday. Keep away from food and drink. Keep away from tobacco products.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Electrical installations / working materials must comply with the technological safety standards.

Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions

: Protect from humidity and water.

Advice on common storage

: Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.


Dampness

: Keep in a dry, cool and well-ventilated place.

Other data

: Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Page 7 / 20	102000031859	A member of  ALтана
-------------	--------------	---

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

This information is not available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
Copper	7440-50-8	AGW (inhalable fraction)	1 mg/m ³		DE TRGS 900
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Inhalable fraction)	10 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				
zinc powder — zinc dust (stabilised)	7440-66-6	AGW (Alveolate fraction)	1,25 mg/m ³	2014-04-02	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)				
Further information	Commission for dangerous substancesSenate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				

8.2 Exposure controls
Personal protective equipment

Eye protection : Safety glasses

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

: Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Leather

Remarks

: Leather gloves
 The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
 The exact break through time can be obtained from the protective glove producer and this has to be observed.
 Recommended preventive skin protection

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Long sleeved clothing
 Safety shoes

: Dust impervious protective suit
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

: Use suitable breathing protection if workplace concentration requires.
 Respirator with a dust filter
 P1 filter

Environmental exposure controls

General advice :

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

- : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform
 respective authorities.
- Water : The product should not be allowed to enter drains, water
 courses or the soil.
- :

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

- Appearance : powder
- Colour : gold
- Odour : odourless
- pH : No data available
- Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : No data available
- Bulk density : No data available
- Flammability (solid, gas) : The substance or mixture is a flammable solid
 with the category 1.
- Auto-flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Vapour pressure	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No hazards to be specially mentioned.

No decomposition if stored and applied as directed.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : No data available

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

Other information : No data available

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****Copper :**Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.**zinc powder — zinc dust (stabilised) :**

Acute oral toxicity : Rat: > 2 000 mg/kg

amines, hydrogenated tallow alkyl :

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Acute oral toxicity : LD50 Rat: > 2 000 - 5 000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation**Product**

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product**

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product**

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****copper (7440-50-8) :**

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

zinc (7440-66-6) :**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Amines, hydrogenated tallow alkyl (61788-45-2) :**Ecotoxicology Assessment**

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.
 In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : 3089
 TDG : 3089
 CFR : 3089
 IMDG : 3089
 IATA : 3089

14.2 Proper shipping name

ADR : METAL POWDER, FLAMMABLE, N.O.S.
 (Gold bronze powder ,Copper metal powder)
 TDG : METAL POWDER, FLAMMABLE, N.O.S.
 (Gold bronze powder ,Copper metal powder)
 CFR : METAL POWDERS, FLAMMABLE, N.O.S.
 (Gold bronze powder ,Copper metal powder)
 IMDG : METAL POWDER, FLAMMABLE, N.O.S.
 (,Gold bronze powder ,Copper metal powder)
 IATA : METAL POWDER, FLAMMABLE, N.O.S.

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

14.3 Transport hazard class

ADR	: 4.1
TDG	: 4.1
CFR	: 4.1
IMDG	: 4.1
IATA	: 4.1

14.4 Packing group**ADR**

Packaging group	: II
Classification Code	: F3
Hazard Identification Number	: 40
Labels	: 4.1
Tunnel restriction code	: (E)

TDG

Packaging group	: II
Labels	: 4.1

CFR

Packaging group	: II
Labels	: 4.1

IMDG

Packaging group	: II
Labels	: 4.1
EmS Number	: F-G, S-G

IATA

Packing instruction (cargo aircraft)	: 448
Packing instruction	: 445

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

(passenger aircraft)

Packing instruction (LQ) : Y441

Packaging group : II

Labels : 4.1

14.5 Environmental hazards

ADR : Environmentally hazardous

IMDG : Marine pollutant

14.6 Special precautions for user

IMDG Code- segregation group:

: IMDG Code segregation group 7 - Heavy metals and their salts

: IMDG Code segregation group 15 - Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Prohibition/Restriction

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Prohibition/Restriction

Regulation (EC) No 850/2004 on persistent organic : Not applicable

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020

pollutants

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H228	: Flammable solid.
H302	: Harmful if swallowed.
H303	: May be harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET



Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

LITHOFLEX XA 15 01 Rich Gold

Version 2.0

Revision Date 10.12.2019

Print Date 06.08.2020
