

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SHINEDECOR 9350 Copper
Material number : 072923HM0

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

Telephone :
Telefax :
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

NCEC:

(contract no.: ECKART29003-NCEC)

+44 1235 239671 (Middle East/Africa, call and response in your language)

+1 215 207 0061 (Americas, call and response in your language)

+65 3158 1074 (Asia-Pacific, call and response in your language)

SECTION 2: Hazards identification

GHS Classification

: Acute toxicity, Category 4, Oral, H302
Skin corrosion/irritation, Category 3, H316
Serious eye damage/eye irritation, Category 2A, H319

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SHINEDECOR 9350 Copper


Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

Short-term (acute) aquatic hazard, Category 1, H400
Long-term (chronic) aquatic hazard, Category 1, H410

GHS-Labeling

Symbol(s)	:	
Signal word	:	Warning
Hazard statements	:	H302: Harmful if swallowed. H316: Causes mild skin irritation. H319: Causes serious eye irritation. H410: Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear eye protection/ face protection. Response: P337 + P313 If eye irritation persists: Get medical advice/ attention. P391 Collect spillage. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
copper	7440-50-8
silicon dioxide	7631-86-9

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

SECTION 3: Composition/information on ingredients

Substance name : shinedecor 9350 ku

Substance No. :

Hazardous components

Chemical name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
Copper	7440-50-8 231-159-6	Acute Tox.;4;H302 ;2A;H319 Aquatic Acute;1;H400 Aquatic Chronic;1;H410	25 - 50
salt of polyamineamide (72243/00/2008.0023, Germany)	Not Assigned	Skin Irrit.;2;H315	1 - 10
silicon dioxide	7631-86-9 231-545-4	Acute Tox.;5;H303	1 - 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical advice.

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

- If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media : Special powder against metal fire, Dry sand, ABC powder
- Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

Pick up and transfer to properly labelled containers.
 Do not flush with water.
 Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Protect from humidity and water.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not store together with oxidizing and self-igniting products.
- Dampness : Keep in a dry, cool and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
Copper	7440-50-8	AGW (inhalable fraction)	1 mg/m ³		DE TRGS 900
silicon dioxide	7631-86-9	AGW (Inhalable fraction)	4 mg/m ³	2013-09-19	DE TRGS 900

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel). When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child
---------------------	--

United States of America (USA):

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
Copper	7440-50-8	TWA	1 mg/m ³	2008-01-01	
Copper	7440-50-8	TWA (dust and mists)	1 mg/m ³	2005-09-01	
Copper	7440-50-8	TWA	1 mg/m ³	1989-01-19	
Copper	7440-50-8	TWA	0,2 mg/m ³	2008-01-01	
Copper	7440-50-8	TWA	0,1 mg/m ³	1989-01-19	
Copper	7440-50-8	TWA (Dust and mist)	1 mg/m ³	2010-03-01	
Copper	7440-50-8	TWA (Fumes)	0,2 mg/m ³	2010-03-01	
Copper	7440-50-8	TWA (Dust)	1 mg/m ³	2013-10-08	
Copper	7440-50-8	TWA (Mist)	1 mg/m ³	2013-10-08	
Copper	7440-50-8	TWA (dusts and mists)	1 mg/m ³	2011-07-01	
Copper	7440-50-8	TWA (Fumes)	0,1 mg/m ³	2011-07-01	
Copper	7440-50-8	TWA (Fumes)	0,1 mg/m ³	1989-01-19	
Copper	7440-50-8	TWA (Dust and mist)	1 mg/m ³	1989-01-19	
Copper	7440-50-8	PEL (Fumes)	0,1 mg/m ³	2014-11-26	

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot	2012-07-01	
silicon dioxide	7631-86-9	TWA (Dust)	80 mg/m ³ / %SiO ₂	2012-07-01	
silicon dioxide	7631-86-9	TWA	6 mg/m ³	2013-10-08	
silicon dioxide	7631-86-9	PEL	6 mg/m ³	2014-11-26	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	TWA (Mist)	5 mg/m ³	2011-07-01	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	TWA (Inhalable fraction)	5 mg/m ³	2013-03-01	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	TWA	5 mg/m ³	1989-01-19	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	TWA (Mist)	5 mg/m ³	2013-10-08	
Distillates (petroleum), solvent-	64741-88-4	ST (Mist)	10 mg/m ³	2013-10-08	

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

refined heavy paraffinic; Baseoil — unspecified					
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	TWA (Mist)	5 mg/m ³	1989-01-19	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil — unspecified	64741-88-4	PEL (particulate)	5 mg/m ³	2014-11-26	

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses
- : Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

protective glove producer and this has to be observed.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Recommended preventive skin protection

Skin should be washed after contact.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
 Equipment should conform to EN 14387

Environmental exposure controls

General advice :

- : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

- Water : The product should not be allowed to enter drains, water courses or the soil.

:

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: No data available
Odour	: characteristic
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 100 °C
Flash point	: > 100 °C
Bulk density	: No data available
Flammability (solid, gas)	: No data available
Auto-flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: No data available
Water solubility	: No data available
Miscibility with water	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products :

Other information : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Components:****Copper :**Acute oral toxicity : The component/mixture is moderately toxic after single
ingestion.**silicon dioxide :**

Acute oral toxicity : LD50 Rat: 5 000 mg/kg

Mouse: 15 000 mg/kg

Acute inhalation toxicity : Rat: 0,139 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5 000 mg/kg

Skin corrosion/irritation**Product**

May cause skin irritation and/or dermatitis.

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

Serious eye damage/eye irritation

Product

Eye irritation

Respiratory or skin sensitisation

No data available

Carcinogenicity

No data available

Toxicity to reproduction/fertility

No data available

Reprod.Tox./Development/Teratogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****copper (7440-50-8) :**

M-Factor : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

silicon dioxide (7631-86-9) :

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 7 600 mg/l

Toxicity to algae : (Chlorella pyrenoidosa (aglae)): 440 mg/l
Exposure time: 72 h**12.2 Persistence and degradability**

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information**14.1 UN number****ADR** : 3082

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG : 3082**IATA** : 3082**14.2 Proper shipping name****ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(,Copper metal powder)**IATA** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(Copper metal powder)**14.3 Transport hazard class****ADR** : 9**TDG**

Not dangerous goods

CFR

Not dangerous goods

IMDG : 9**IATA** : 9

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

14.4 Packing group**ADR**

Packaging group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

TDG

Not dangerous goods

CFR

Not dangerous goods

IMDG

Packaging group : III
Labels : 9
EmS Number : F-A, S-F

IATA

Packing instruction (cargo
aircraft) : 964
Packing instruction
(passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packaging group : III
Labels : 9

14.5 Environmental hazards

ADR : Environmentally hazardous

IMDG : Marine pollutant

14.6 Special precautions for user

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Full text of H-Statements**

H302 : Harmful if swallowed.
H303 : May be harmful if swallowed.
H315 : Causes skin irritation.

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)

SHINEDECOR 9350 Copper

Version 4.1

Revision Date 12.03.2020

Print Date 07.08.2020

H316 : Causes mild skin irritation.
H319 : Causes serious eye irritation.
H400 : Very toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.