

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Concentrate Copper 200 kgs 16-08034
Product code : 08074925V

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company :

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

Long-term (chronic) aquatic hazard,
Category 1

H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Solvent naphtha (petroleum), light arom.
copper flakes (coated with aliphatic acid)
xylene
n-butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version
3.2

Revision Date:
27.04.2020

SDS Number:
102000000122

Print Date: 08.08.2020
Date of first issue: 11.04.2017

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
copper flakes (coated with aliphatic acid)	Not Assigned	Acute Tox. 4; H302 Acute Tox. 3; H331 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 10 - < 20
xylene	1330-20-7 215-535-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
amines, hydrogenated tallow alkyl	61788-45-2 (90640-32-7) 262-976-6	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.025 - < 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move the victim to fresh air.

Move out of dangerous area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version
3.2

Revision Date:
27.04.2020

SDS Number:
102000000122

Print Date: 08.08.2020
Date of first issue: 11.04.2017

- Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.

If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Special powder against metal fire
Dry sand
ABC powder
- Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
3.2	27.04.2020	102000000122	Date of first issue: 11.04.2017

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored separately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Pick up and transfer to properly labelled containers.

Do not flush with water.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
3.2	27.04.2020	102000000122	Date of first issue: 11.04.2017

vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition. No smoking.

Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : General industrial hygiene practice.

When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from sources of ignition - No smoking. Do not store near combustible materials. Keep containers tightly closed in a cool, well-ventilated place. To maintain product quality, do not store in heat or direct sunlight.

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

strongly acid materials in order to avoid exothermic reactions.
Do not store together with oxidizing and self-igniting products.

Dampness : Keep in a dry, cool and well-ventilated place.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
copper flakes (coated with aliphatic acid)	Not Assigned	TWA (Fumes)	0.2 mg/m ³ (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m ³ (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m ³ (Copper)	GB EH40
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 220 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole	After shift	GB EH40 BAT

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version
3.2

Revision Date:
27.04.2020

SDS Number:
102000000122

Print Date: 08.08.2020
Date of first issue: 11.04.2017

		Creatinine (Urine)		
--	--	-----------------------	--	--

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Solvent naphtha (petroleum), light arom.	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Workers	Skin contact	Long-term systemic effects	25 mg/kg
xylene	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg
	Consumers	Ingestion	Long-term systemic effects	12.5 mg/kg
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
n-butyl acetate	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg
	Workers	Inhalation	Long-term systemic effects	48 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Skin contact	Acute systemic effects	11 mg/kg
Consumers	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Long-term local effects	35.7 mg/m ³
	Consumers	Skin contact	Acute systemic effects	6 mg/kg
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg
	Consumers	Ingestion	Acute systemic effects	2 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
copper flakes (coated with	Soil	65.5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

aliphatic acid)	Fresh water	0.0078 mg/l
	Fresh water sediment	87 mg/kg
	Marine water	0.0052 mg/l
	Marine sediment	676 mg/kg
	STP	0.230 mg/l
xylene	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Fresh water sediment	13.7 mg/l
	Marine sediment	1.37 mg/l
	Soil	2.68 mg/l
	Secondary Poisoning	20 mg/kg
n-butyl acetate	STP	9.6 mg/l
	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	STP	35.6 mg/l
	Fresh water sediment	0.981 mg/kg
	Marine sediment	0.098 mg/kg
	Soil	0.090 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2	Revision Date: 27.04.2020	SDS Number: 102000000122	Print Date: 08.08.2020 Date of first issue: 11.04.2017
----------------	------------------------------	-----------------------------	---

Equipment should conform to EN 14387

In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: No data available
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 124 °C
Flash point	: 30 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Auto-ignition temperature	: No data available
Smoldering temperature	: No data available
Decomposition temperature	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version	Revision Date:	SDS Number:	Print Date:
3.2	27.04.2020	102000000122	08.08.2020
			Date of first issue: 11.04.2017

Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 1.05 g/cm ³
Bulk density	: No data available
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: see user defined free text
Viscosity, kinematic	: > 21 mm ² /s (40 °C)
Flow time	: 13 - 16 s at 20 °C Cross section: 4 mm Method: DIN 53211

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

Heat, flames and sparks.

10.5 Incompatible materials

10.6 Hazardous decomposition products

Thermal decomposition : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 2.81 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat): 3,492 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

copper flakes (coated with aliphatic acid):

Acute oral toxicity : LD50 Oral (Rat, male and female): 300 - 500 mg/kg
Method: OECD Test Guideline 423
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat, male): 0.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version
3.2

Revision Date:
27.04.2020

SDS Number:
102000000122

Print Date: 08.08.2020
Date of first issue: 11.04.2017

xylene:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

amines, hydrogenated tallow alkyl:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

xylene:

Result: Skin irritation

amines, hydrogenated tallow alkyl:

Result: Skin irritation

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Eye irritation

Components:

copper flakes (coated with aliphatic acid):

Result: Eye irritation

xylene:

Result: Eye irritation

amines, hydrogenated tallow alkyl:

Result: Irreversible effects on the eye

Remarks: May cause irreversible eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version
3.2

Revision Date:
27.04.2020

SDS Number:
102000000122

Print Date: 08.08.2020
Date of first issue: 11.04.2017

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum), light arom.:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

xylene:

Assessment: May cause respiratory irritation.

n-butyl acetate:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

xylene:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

amines, hydrogenated tallow alkyl:

Target Organs: Liver, Gastrointestinal tract, Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum), light arom.:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

May be fatal if swallowed and enters airways.

xylene:

May be fatal if swallowed and enters airways.

amines, hydrogenated tallow alkyl:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

Components:

amines, hydrogenated tallow alkyl:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Solvent naphtha (petroleum), light arom.:

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

copper flakes (coated with aliphatic acid):

M-Factor (Short-term (acute) aquatic hazard) : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

amines, hydrogenated tallow alkyl:

M-Factor (Short-term (acute) aquatic hazard) : 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

M-Factor (Long-term (chronic) aquatic hazard) : 10

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Components:

amines, hydrogenated tallow alkyl:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

European Waste Catalogue : 16 05 04 - gases in pressure containers (including halons) containing dangerous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
(, Copper metal powder)
IMDG : PAINT
(Copper metal powder)
IATA : Paint

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 46.7 %, 490.38 g/l

15.2 Chemical safety assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version 3.2 Revision Date: 27.04.2020 SDS Number: 102000000122 Print Date: 08.08.2020
Date of first issue: 11.04.2017

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Concentrate Copper 200 kgs 16-08034

Version	Revision Date:	SDS Number:	Print Date: 08.08.2020
3.2	27.04.2020	102000000122	Date of first issue: 11.04.2017

inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN