

**Date of impression** 18.11.2020/09:40:02  
**page/of** 1/1

**edition** 15.11.2020

**material denomination** **HYDROSHINE WS 4140**  
**material-no.** 021979AN0  
**material description** Effect pigment dispersion based on highly brilliant  
 PVD-aluminium-pigments with a heavy metal free encapsulation

The solvent contained is isopropanol / butylglykol

Pigmentcomposition:  
 aluminium appr. 8,4%  
 coating appr. 1,6%

**material specification**

<b>insp. characteristic</b>	<b>specification</b>	<b>unit</b>
T100004 pigment content / non volatile	8,5 - 11,5	%
T100004 volatile content	88,5 - 91,5	%
T100289 aqueous paint spray-out	pass	
T100489 D 50	12,5 - 15,5	µm

total shelf life in month: 24

EC-safety data sheet-no. 021979AN0

The Data on this technical information sheet correspond with the current status of our knowledge and experience.  
 The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights.

We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.

Draft	Approval	Release
Technical services	Production	Quality control
15.11.2020	15.11.2020	15.11.2020

This document has been printed automatically and will not be signed.